

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA 50MG<br>STSH4A00 |
| User ID :        | yu98249       | Batch NO. :          | SHM2502650              |
| Print Interval : | 50000 Tablets | Running Time :       | 20 Hour 17 Min 15 Sec   |
| Total Counter :  | 5253714       | Total Running Time : | 2023 Hour 54 Min        |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 42       | %       | Manual ;           | 30           | RPM       |
| Filling Cam :                      |             | Cam B    |         | Cam Range :        | Min :        | 2.50 mm   |
|                                    |             | 4.5-10mm |         |                    | Max :        | 8.00 mm   |
| Target Quantity :                  |             | 6000000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 80       | Min     | Supply Time ;      | 0.5          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 20       | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 60.0     | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 16.01    | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 15.39    | kN      | Yes 10             | Rotations 20 | Tablets   |
| HCP :                              | 1.5 %       | 12.50    | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 12.31    | kN      |                    |              |           |
| LCP :                              | 1.5 %       | 12.13    | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 9.23     | kN      | No 35              | Rotations 35 | Tablets   |
| LSP :                              | 30.0 %      | 8.62     | kN      | No                 |              |           |
| SD limit :                         | 35.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 30.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.75       | kN  | Min : | 1.64       | kN  | Punch NO.; | 59 |
| SD :                 | 1.90       | %   | Max : | 1.82       | kN  | Punch NO.; | 4  |
| Mean Main Pressure : | 12.20      | kN  | Min : | 10.81      | kN  | Punch NO.; | 59 |
| SD :                 | 3.80       | %   | Max : | 13.10      | kN  | Punch NO.; | 72 |
| Filling Depth :      | Increase ; | 728 | Times | Decrease ; | 692 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 12       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.59    | mm  | Pre Thickness ;  | 2.60     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.15    | mm  | Main Thickness ; | 2.15     | mm           |
| Filling Depth :               | 5.89    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.791   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 80      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 20      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | On       |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.21 | kN |             |    |
|                  | Max ;     | 0.38 | kN | Max Punch ; | 63 |
| Lower Punch :    | Average ; | 0.07 | kN |             |    |
|                  | Max ;     | 0.09 | kN | Max Punch ; | 7  |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                     |         |       |          |         |
|-----------------|---------------------|---------|-------|----------|---------|
| Total Counter : | 5253714             | Tablets |       |          |         |
| A.W.C Counter : | 5247780             | Tablets |       |          |         |
| HEP :           | 1 (0.0%)            | Tablets | LEP : | 1 (0.0%) | Tablets |
| GOOD :          | 5247778<br>(100.0%) | Tablets |       |          |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA 50MG<br>STSH4A00 |
| User ID :        | yu98249       | Batch NO. :          | SHM2502650              |
| Print Interval : | 50000 Tablets | Running Time :       | 20 Hour 17 Min 15 Sec   |
| Total Counter :  | 5253714       | Total Running Time : | 2023 Hour 54 Min        |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 42                | %       | Manual ;           | 30           | RPM       |
| Filling Cam :                      |        | Cam B<br>4.5-10mm |         | Cam Range :        | Min :        | 2.50 mm   |
| Target Quantity :                  |        | 6000000           | Tablets |                    | Max :        | 8.00 mm   |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 80                | Min     | Supply Time ;      | 0.5          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 20                | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 1.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 17.37             | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 16.70             | kN      | Yes 10             | Rotations 20 | Tablets   |
| HCP :                              | 1.5 %  | 13.56             | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 13.36             | kN      |                    |              |           |
| LCP :                              | 1.5 %  | 13.16             | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 10.02             | kN      | Yes 35             | Rotations 35 | Tablets   |
| LSP :                              | 30.0 % | 9.35              | kN      | No                 |              |           |
| SD limit :                         | 35.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 30.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | N      |                   |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.86       | kN  | Min : | 1.77       | kN  | Punch NO.; | 4  |
| SD :                 | 1.90       | %   | Max : | 1.94       | kN  | Punch NO.; | 46 |
| Mean Main Pressure : | 13.45      | kN  | Min : | 12.29      | kN  | Punch NO.; | 4  |
| SD :                 | 3.50       | %   | Max : | 14.65      | kN  | Punch NO.; | 5  |
| Filling Depth :      | Increase ; | 307 | Times | Decrease ; | 355 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 12       | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.49    | mm  | Pre Thickness ;  | 2.49     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.22    | mm  | Main Thickness ; | 2.23     | mm           |
| Filling Depth :               | 5.72    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.791   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 80      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 20      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | On       |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.21 | kN |             |    |
|                  | Max ;     | 0.37 | kN | Max Punch ; | 63 |
| Lower Punch :    | Average ; | 0.07 | kN |             |    |
|                  | Max ;     | 0.09 | kN | Max Punch ; | 7  |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                     |         |       |          |         |
|-----------------|---------------------|---------|-------|----------|---------|
| Total Counter : | 5253714             | Tablets |       |          |         |
| A.W.C Counter : | 5247780             | Tablets |       |          |         |
| HEP :           | 1 (0.0%)            | Tablets | LEP : | 1 (0.0%) | Tablets |
| GOOD :          | 5247778<br>(100.0%) | Tablets |       |          |         |