

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pr190041	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	10 Hour 57 Min 53 Sec
Total Counter :	2829778	Total Running Time :	2037 Hour 41 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.49	kN	No		
HEP :	25.0 %	17.78	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	14.44	kN	Yes 15	Times	
Ref :		14.22	kN			
LCP :	1.5 %	14.01	kN	Yes 15	Times	
LEP :	25.0 %	10.67	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.96	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.44	kN	Min :	1.40	kN	Punch NO.;	46
SD :	1.30	%	Max :	1.49	kN	Punch NO.;	18
Mean Main Pressure :	14.18	kN	Min :	12.37	kN	Punch NO.;	8
SD :	4.60	%	Max :	15.67	kN	Punch NO.;	59
Filling Depth :	Increase ; 76	Times	Decrease ;	184	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.19	mm	Main Thickness ;	2.20	mm
Filling Depth :	5.99	mm	Current Cam :	Cam B	
Main Air pressure :	0.759	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	68	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.17	kN	Max Punch ;	41
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	13
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.07	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	2829778	Tablets			
A.W.C Counter :	2810212	Tablets			
HEP :	312 (0.0%)	Tablets	LEP :	1411 (0.1%)	Tablets
GOOD :	2808489 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pr190041	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	10 Hour 57 Min 53 Sec
Total Counter :	2829778	Total Running Time :	2037 Hour 41 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.33	kN	No		
HEP :	25.0 %	16.66	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.53	kN	Yes 15	Times	
Ref :		13.33	kN			
LCP :	1.5 %	13.13	kN	Yes 15	Times	
LEP :	25.0 %	10.00	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	9.33	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.09	kN	Min :	1.05	kN	Punch NO.;	3
		1.80	%	Max :	1.13	kN	Punch NO.;	21
Mean Main Pressure :		13.24	kN	Min :	11.75	kN	Punch NO.;	43
	SD :	4.60	%	Max :	14.67	kN	Punch NO.;	73
Filling Depth :	Increase ;	66	Times	Decrease ;	80	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.24	mm
Filling Depth :	5.54	mm	Current Cam :	Cam B	
Main Air pressure :	0.759	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	68	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.19	kN	Max Punch ;	31
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	13
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.07	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	2829778	Tablets			
A.W.C Counter :	2810212	Tablets			
HEP :	312 (0.0%)	Tablets	LEP :	1411 (0.1%)	Tablets
GOOD :	2808489 (99.9%)	Tablets			