

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pr190041	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	14 Hour 38 Min 13 Sec
Total Counter :	3780522	Total Running Time :	2041 Hour 21 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.49	kN	No		
HEP :	25.0 %	17.78	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	14.44	kN	Yes 15	Times	
Ref :		14.22	kN			
LCP :	1.5 %	14.01	kN	Yes 15	Times	
LEP :	25.0 %	10.67	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.96	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.45	kN	Min :	1.40	kN	Punch NO.;	59
SD :	1.60	%	Max :	1.51	kN	Punch NO.;	29
Mean Main Pressure :	14.32	kN	Min :	12.30	kN	Punch NO.;	13
SD :	5.70	%	Max :	15.88	kN	Punch NO.;	59
Filling Depth :	Increase ;	136	Times	Decrease ;	249	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.22	mm	Main Thickness ;	2.23	mm
Filling Depth :	6.03	mm	Current Cam :	Cam B	
Main Air pressure :	0.764	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.16	kN	Max Punch ;	45
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	31
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.06	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	3780522	Tablets			
A.W.C Counter :	3759718	Tablets			
HEP :	442 (0.0%)	Tablets	LEP :	1610 (0.0%)	Tablets
GOOD :	3757666 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pr190041	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	14 Hour 38 Min 13 Sec
Total Counter :	3780522	Total Running Time :	2041 Hour 21 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.46	kN	No		
HEP :	25.0 %	17.75	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	14.41	kN	Yes 15	Times	
Ref :		14.20	kN			
LCP :	1.5 %	13.99	kN	Yes 15	Times	
LEP :	25.0 %	10.65	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	9.94	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.13	kN	Min :	1.06	kN	Punch NO.;	44
SD :	2.00	%	Max :	1.18	kN	Punch NO.;	62
Mean Main Pressure :	14.17	kN	Min :	12.45	kN	Punch NO.;	6
SD :	4.30	%	Max :	15.62	kN	Punch NO.;	68
Filling Depth :	Increase ;	111	Times	Decrease ;	129	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.25	mm	Main Thickness ;	2.26	mm
Filling Depth :	5.54	mm	Current Cam :	Cam B	
Main Air pressure :	0.764	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.16	kN	Max Punch ;	45
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	33
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	3780522	Tablets			
A.W.C Counter :	3759795	Tablets			
HEP :	442 (0.0%)	Tablets	LEP :	1610 (0.0%)	Tablets
GOOD :	3757743 (99.9%)	Tablets			