

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	16 Hour 34 Min 09 Sec
Total Counter :	4280796	Total Running Time :	2043 Hour 18 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.49	kN	No		
HEP :	25.0 %	17.78	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	14.44	kN	Yes 15	Times	
Ref :		14.22	kN			
LCP :	1.5 %	14.01	kN	Yes 15	Times	
LEP :	25.0 %	10.67	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.96	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.49	kN	Min :	1.44	kN	Punch NO.;	43
SD :	1.70	%	Max :	1.55	kN	Punch NO.;	17
Mean Main Pressure :	14.40	kN	Min :	12.39	kN	Punch NO.;	46
SD :	6.00	%	Max :	16.42	kN	Punch NO.;	68
Filling Depth :	Increase ; 181	Times	Decrease ; 275	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.24	mm
Filling Depth :	6.12	mm	Current Cam :	Cam B	
Main Air pressure :	0.756	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	52	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.16	kN	Max Punch ;	42
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	53
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	4280796	Tablets			
A.W.C Counter :	4259756	Tablets			
HEP :	442 (0.0%)	Tablets	LEP :	1610 (0.0%)	Tablets
GOOD :	4257704 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	16 Hour 34 Min 09 Sec
Total Counter :	4280796	Total Running Time :	2043 Hour 18 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.61	kN	No		
HEP :	25.0 %	17.90	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	14.53	kN	Yes 15	Times	
Ref :		14.32	kN			
LCP :	1.5 %	14.10	kN	Yes 15	Times	
LEP :	25.0 %	10.74	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	10.02	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.14	kN	Min :	1.11	kN	Punch NO.;	39
SD :	1.70	%	Max :	1.19	kN	Punch NO.;	6
Mean Main Pressure :	14.43	kN	Min :	12.09	kN	Punch NO.;	46
SD :	4.70	%	Max :	16.54	kN	Punch NO.;	73
Filling Depth :	Increase ;	126	Times	Decrease ;	148	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.26	mm	Main Thickness ;	2.27	mm
Filling Depth :	5.60	mm	Current Cam :	Cam B	
Main Air pressure :	0.756	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	52	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.16	kN	Max Punch ;	42
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	45
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	9

Tablet Data (N/A)

Total Counter :	4280796	Tablets			
A.W.C Counter :	4259756	Tablets			
HEP :	442 (0.0%)	Tablets	LEP :	1610 (0.0%)	Tablets
GOOD :	4257704 (100.0%)	Tablets			