

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502850
Print Interval :	50000 Tablets	Running Time :	10 Hour 35 Min 58 Sec
Total Counter :	2601778	Total Running Time :	2060 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.11	kN	No		
HEP :	25.0 %	16.45	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.36	kN	Yes 15	Times	
Ref :		13.16	kN			
LCP :	1.5 %	12.97	kN	Yes 15	Times	
LEP :	25.0 %	9.87	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.21	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.41	kN	Min :	1.38	kN	Punch NO.;	39
SD :	1.30	%	Max :	1.47	kN	Punch NO.;	17
Mean Main Pressure :	13.20	kN	Min :	11.78	kN	Punch NO.;	10
SD :	4.70	%	Max :	14.35	kN	Punch NO.;	63
Filling Depth :	Increase ; 364	Times	Decrease ;	433	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.25	mm	Main Thickness ;	2.26	mm
Filling Depth :	5.93	mm	Current Cam :	Cam B	
Main Air pressure :	0.787	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	66	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	31
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	36
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.13	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	2601778	Tablets			
A.W.C Counter :	2596417	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	2596392 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502850
Print Interval :	50000 Tablets	Running Time :	10 Hour 35 Min 58 Sec
Total Counter :	2601778	Total Running Time :	2060 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.15	kN	No		
HEP :	25.0 %	16.49	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.39	kN	Yes 15	Times	
Ref :		13.19	kN			
LCP :	1.5 %	12.99	kN	Yes 15	Times	
LEP :	25.0 %	9.89	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	9.23	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.07	kN	Min :	1.04	kN	Punch NO.;	10
		1.70	%	Max :	1.13	kN	Punch NO.;	17
Mean Main Pressure :		13.36	kN	Min :	11.51	kN	Punch NO.;	33
	SD :	4.30	%	Max :	14.96	kN	Punch NO.;	56
Filling Depth :	Increase ;	418	Times	Decrease ;	433	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.28	mm	Main Thickness ;	2.29	mm
Filling Depth :	5.35	mm	Current Cam :	Cam B	
Main Air pressure :	0.787	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	66	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	31
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	36
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.13	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	2601778	Tablets			
A.W.C Counter :	2596417	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	2596392 (100.0%)	Tablets			