

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	rp98927	Batch NO. :	HAM2501150
Print Interval :	50000 Tablets	Running Time :	04 Hour 29 Min 58 Sec
Total Counter :	450166	Total Running Time :	2086 Hour 8 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.43	kN	No		
HEP :	25.0 %	13.88	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	11.33	kN	Yes 15	Times	
Ref :		11.10	kN			
LCP :	2.0 %	10.88	kN	Yes 15	Times	
LEP :	25.0 %	8.33	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	7.77	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.94	kN	Min :	0.92	kN	Punch NO.;	1
SD :	0.90	%	Max :	0.96	kN	Punch NO.;	28
Mean Main Pressure :	11.23	kN	Min :	10.22	kN	Punch NO.;	46
SD :	5.00	%	Max :	12.63	kN	Punch NO.;	19
Filling Depth :	Increase ;	1427	Times	Decrease ;	1251	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	2.45	mm
Filling Depth :	8.47	mm	Current Cam :	Cam C	
Main Air pressure :	0.800	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	78	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.12	kN	Max Punch ;	13
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	46
Ejection Force :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	450166	Tablets			
A.W.C Counter :	445781	Tablets			
HEP :	390 (0.1%)	Tablets	LEP :	660 (0.1%)	Tablets
GOOD :	444731 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	rp98927	Batch NO. :	HAM2501150
Print Interval :	50000 Tablets	Running Time :	04 Hour 29 Min 58 Sec
Total Counter :	450166	Total Running Time :	2086 Hour 8 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	85	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.69	kN	No		
HEP :	25.0 %	12.20	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	9.95	kN	Yes 20	Times	
Ref :		9.76	kN			
LCP :	2.0 %	9.56	kN	Yes 20	Times	
LEP :	25.0 %	7.32	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	6.83	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.70	kN	Min :	0.68	kN	Punch NO.;	19
SD :	1.40	%	Max :	0.73	kN	Punch NO.;	51
Mean Main Pressure :	9.56	kN	Min :	8.69	kN	Punch NO.;	46
SD :	3.80	%	Max :	10.36	kN	Punch NO.;	37
Filling Depth :	Increase ;	1014	Times	Decrease ;	972	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	2.66	mm
Filling Depth :	7.53	mm	Current Cam :	Cam C	
Main Air pressure :	0.800	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	78	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.12	kN	Max Punch ;	13
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	46
Ejection Force :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	22

Tablet Data (N/A)

Total Counter :	450166	Tablets			
A.W.C Counter :	445781	Tablets			
HEP :	390 (0.1%)	Tablets	LEP :	660 (0.1%)	Tablets
GOOD :	444731 (99.8%)	Tablets			