

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Gaba800mg STJD1B00
User ID :	mr99799	Batch NO. :	JDM2501280
Print Interval :	50000 Tablets	Running Time :	01 Hour 09 Min 36 Sec
Total Counter :	116194	Total Running Time :	2098 Hour 54 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	165	%	Manual ;	30	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		120000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.91	kN	No		
HEP :	25.0 %	23.95	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	19.55	kN	Yes 15	Times	
Ref :		19.16	kN			
LCP :	2.0 %	18.78	kN	Yes 15	Times	
LEP :	25.0 %	14.37	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	13.41	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.23	kN	Min :	2.09	kN	Punch NO.;	43
SD :	3.10	%	Max :	2.39	kN	Punch NO.;	23
Mean Main Pressure :	19.41	kN	Min :	18.16	kN	Punch NO.;	45
SD :	2.30	%	Max :	20.19	kN	Punch NO.;	10
Filling Depth :	Increase ; 21	Times	Decrease ; 24	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.60	mm	Main Thickness ;	4.61	mm
Filling Depth :	11.51	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.791	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	55	Min			
Lower Punch Remain Time (S2):	37	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.33	kN		
	Max ;	0.37	kN	Max Punch ;	6
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.21	kN	Max Punch ;	23
Ejection Force :	Average ;	0.10	kN		
	Max ;	0.21	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	116194	Tablets			
A.W.C Counter :	113155	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	113155 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Gaba800mg STJD1B00
User ID :	mr99799	Batch NO. :	JDM2501280
Print Interval :	50000 Tablets	Running Time :	01 Hour 09 Min 36 Sec
Total Counter :	116194	Total Running Time :	2098 Hour 54 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	180	%	Manual ;	30	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		120000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.56	kN	No		
HEP :	25.0 %	24.58	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	20.05	kN	Yes 20	Times	
Ref :		19.66	kN			
LCP :	2.0 %	19.27	kN	Yes 20	Times	
LEP :	25.0 %	14.75	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	13.76	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.95	kN	Min :	1.82	kN	Punch NO.;	16
SD :	3.50	%	Max :	2.16	kN	Punch NO.;	23
Mean Main Pressure :	19.80	kN	Min :	18.91	kN	Punch NO.;	15
SD :	2.20	%	Max :	20.87	kN	Punch NO.;	9
Filling Depth :	Increase ; 6	Times	Decrease ; 19	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.73	mm	Main Thickness ;	4.74	mm
Filling Depth :	12.36	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.791	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	55	Min			
Lower Punch Remain Time (S2):	37	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.33	kN		
	Max ;	0.37	kN	Max Punch ;	6
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.21	kN	Max Punch ;	23
Ejection Force :	Average ;	0.10	kN		
	Max ;	0.21	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	116194	Tablets			
A.W.C Counter :	113155	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	113155 (100.0%)	Tablets			