

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Tams0.4mg STUL2A00
User ID :	am98755	Batch NO. :	ULM2501904
Print Interval :	50000 Tablets	Running Time :	00 Hour 20 Min 23 Sec
Total Counter :	50082	Total Running Time :	2099 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2400000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.67	kN	No		
HEP :	25.0 %	17.95	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	14.65	kN	Yes 15	Times	
Ref :		14.36	kN			
LCP :	2.0 %	14.07	kN	Yes 15	Times	
LEP :	25.0 %	10.77	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	10.05	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.07	kN	Min :	2.06	kN	Punch NO.;	2
		0.50	%	Max :	2.11	kN	Punch NO.;	48
Mean Main Pressure :		14.44	kN	Min :	13.21	kN	Punch NO.;	19
	SD :	3.50	%	Max :	15.49	kN	Punch NO.;	28
Filling Depth :	Increase ;	33	Times	Decrease ;	50	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.20	mm	Main Thickness ;	2.21	mm
Filling Depth :	7.94	mm	Current Cam :	Cam C	
Main Air pressure :	0.794	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.40	kN		
	Max ;	0.45	kN	Max Punch ;	31
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	9
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	50082	Tablets			
A.W.C Counter :	42591	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	42588 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : am98755 Print Interval : 50000 Tablets Total Counter : 50082 Station : Station 2	Product Name : Tams0.4mg STUL2A00 Batch NO. : ULM2501904 Running Time : 00 Hour 20 Min 23 Sec Total Running Time : 2099 Hour 16 Min
---	--

Setting Value

Feeder :	Auto ;	74	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		2400000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) :		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) :		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.94	kN	No		
HEP :	25.0 %	16.28	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	13.29	kN	Yes 20	Times	
Ref :		13.03	kN			
LCP :	2.0 %	12.77	kN	Yes 20	Times	
LEP :	25.0 %	9.77	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	9.12	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.27	kN	Min :	2.23	kN	Punch NO.;	25
		0.80	%	Max :	2.32	kN	Punch NO.;	42
Mean Main Pressure :		13.20	kN	Min :	11.30	kN	Punch NO.;	22
	SD :	5.40	%	Max :	14.80	kN	Punch NO.;	28
Filling Depth :	Increase ;	15	Times	Decrease ;	30	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.91	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	8.02	mm	Current Cam :	Cam C	
Main Air pressure :	0.794	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.40	kN		
	Max ;	0.44	kN	Max Punch ;	45
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	9
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	50082	Tablets			
A.W.C Counter :	42591	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	42588 (100.0%)	Tablets			