

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Tams0.4mg STUL2A00
User ID :	am98755	Batch NO. :	ULM2501904
Print Interval :	50000 Tablets	Running Time :	03 Hour 48 Min 18 Sec
Total Counter :	600256	Total Running Time :	2102 Hour 44 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2400000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.24	kN	No		
HEP :	25.0 %	18.50	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	15.10	kN	Yes 15	Times	
Ref :		14.80	kN			
LCP :	2.0 %	14.51	kN	Yes 15	Times	
LEP :	25.0 %	11.10	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	10.36	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.98	kN	Min :	1.96	kN	Punch NO.;	7
SD :	0.40	%	Max :	2.00	kN	Punch NO.;	8
Mean Main Pressure :	14.72	kN	Min :	12.95	kN	Punch NO.;	19
SD :	4.30	%	Max :	15.87	kN	Punch NO.;	13
Filling Depth :	Increase ; 81	Times	Decrease ;	109	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.25	mm	Main Thickness ;	2.26	mm
Filling Depth :	8.50	mm	Current Cam :	Cam C	
Main Air pressure :	0.762	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.29	kN		
	Max ;	0.35	kN	Max Punch ;	49
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	53
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	600256	Tablets			
A.W.C Counter :	592784	Tablets			
HEP :	4 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	592780 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Tams0.4mg STUL2A00
User ID :	am98755	Batch NO. :	ULM2501904
Print Interval :	50000 Tablets	Running Time :	03 Hour 48 Min 18 Sec
Total Counter :	600256	Total Running Time :	2102 Hour 44 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	74	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2400000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.20	kN	No		
HEP :	25.0 %	17.50	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	14.28	kN	Yes 20	Times	
Ref :		14.00	kN			
LCP :	2.0 %	13.72	kN	Yes 20	Times	
LEP :	25.0 %	10.50	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	9.80	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.20	kN	Min :	2.15	kN	Punch NO.;	35
SD :	0.70	%	Max :	2.24	kN	Punch NO.;	53
Mean Main Pressure :	14.18	kN	Min :	11.76	kN	Punch NO.;	19
SD :	5.70	%	Max :	15.81	kN	Punch NO.;	26
Filling Depth :	Increase ; 65	Times	Decrease ;	86	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.91	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.43	mm	Main Thickness ;	2.44	mm
Filling Depth :	8.17	mm	Current Cam :	Cam C	
Main Air pressure :	0.762	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.29	kN		
	Max ;	0.35	kN	Max Punch ;	49
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	53
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	600256	Tablets			
A.W.C Counter :	592784	Tablets			
HEP :	4 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	592780 (100.0%)	Tablets			