

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICL 400MG,STVI1B00
User ID :	pb97604	Batch NO. :	VIM2500940
Print Interval :	50000 Tablets	Running Time :	00 Hour 35 Min 07 Sec
Total Counter :	100088	Total Running Time :	2113 Hour 50 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.01	kN	No		
HEP :	25.0 %	18.28	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	14.92	kN	Yes 15	Times	
Ref :		14.63	kN			
LCP :	2.0 %	14.33	kN	Yes 15	Times	
LEP :	25.0 %	10.97	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	10.24	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.54	kN	Min :	2.49	kN	Punch NO.;	40
SD :	1.10	%	Max :	2.61	kN	Punch NO.;	30
Mean Main Pressure :	14.62	kN	Min :	13.94	kN	Punch NO.;	24
SD :	2.10	%	Max :	15.40	kN	Punch NO.;	61
Filling Depth :	Increase ; 0	Times	Decrease ; 5	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.25	mm	Main Thickness ;	2.75	mm
Filling Depth :	7.98	mm	Current Cam :	Cam C	
Main Air pressure :	0.785	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.14	kN	Max Punch ;	25
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.21	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	62

Tablet Data (N/A)

Total Counter :	100088	Tablets			
A.W.C Counter :	96649	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	96649 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICL 400MG,STVI1B00
User ID :	pb97604	Batch NO. :	VIM2500940
Print Interval :	50000 Tablets	Running Time :	00 Hour 35 Min 07 Sec
Total Counter :	100088	Total Running Time :	2113 Hour 50 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.86	kN	No		
HEP :	25.0 %	18.13	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	14.80	kN	Yes 20	Times	
Ref :		14.51	kN			
LCP :	2.0 %	14.22	kN	Yes 20	Times	
LEP :	25.0 %	10.88	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	10.15	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.66	kN	Min :	2.59	kN	Punch NO.;	6
SD :	1.50	%	Max :	2.77	kN	Punch NO.;	61
Mean Main Pressure :	14.69	kN	Min :	14.07	kN	Punch NO.;	11
SD :	2.30	%	Max :	15.54	kN	Punch NO.;	25
Filling Depth :	Increase ; 0	Times	Decrease ; 1	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.45	mm	Main Thickness ;	2.95	mm
Filling Depth :	8.12	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.785	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	20
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.21	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	62

Tablet Data (N/A)

Total Counter :	100088	Tablets			
A.W.C Counter :	96649	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	96649 (100.0%)	Tablets			