

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICL 400MG,STVI1B00
User ID :	rp98927	Batch NO. :	VIM2500940
Print Interval :	50000 Tablets	Running Time :	07 Hour 52 Min 42 Sec
Total Counter :	1350620	Total Running Time :	2121 Hour 9 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.18	kN	No		
HEP :	25.0 %	18.44	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	15.05	kN	Yes 15	Times	
Ref :		14.75	kN			
LCP :	2.0 %	14.46	kN	Yes 15	Times	
LEP :	25.0 %	11.06	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	10.33	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.48	kN	Min :	2.42	kN	Punch NO.;	41
SD :	1.20	%	Max :	2.54	kN	Punch NO.;	27
Mean Main Pressure :	14.94	kN	Min :	14.25	kN	Punch NO.;	52
SD :	2.10	%	Max :	15.79	kN	Punch NO.;	27
Filling Depth :	Increase ; 0	Times	Decrease ; 7	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.25	mm	Main Thickness ;	2.75	mm
Filling Depth :	8.00	mm	Current Cam :	Cam C	
Main Air pressure :	0.800	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.09	kN	Max Punch ;	27
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.26	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1350620	Tablets			
A.W.C Counter :	1347184	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1347184 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICL 400MG,STVI1B00
User ID :	rp98927	Batch NO. :	VIM2500940
Print Interval :	50000 Tablets	Running Time :	07 Hour 52 Min 42 Sec
Total Counter :	1350620	Total Running Time :	2121 Hour 9 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.61	kN	No		
HEP :	25.0 %	18.86	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	15.39	kN	Yes 20	Times	
Ref :		15.08	kN			
LCP :	2.0 %	14.78	kN	Yes 20	Times	
LEP :	25.0 %	11.31	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	10.56	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.61	kN	Min :	2.53	kN	Punch NO.;	32
SD :	1.30	%	Max :	2.68	kN	Punch NO.;	43
Mean Main Pressure :	15.34	kN	Min :	14.58	kN	Punch NO.;	11
SD :	2.20	%	Max :	16.20	kN	Punch NO.;	25
Filling Depth :	Increase ; 0	Times	Decrease ; 6	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.42	mm	Main Thickness ;	2.92	mm
Filling Depth :	8.09	mm	Current Cam :	Cam C	
Main Air pressure :	0.800	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.09	kN	Max Punch ;	27
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.24	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1350620	Tablets			
A.W.C Counter :	1347184	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1347184 (100.0%)	Tablets			