

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 800MG STIU2D00
User ID :	sj97904	Batch NO. :	IUM2500880
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 53 Sec
Total Counter :	50018	Total Running Time :	2122 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	30	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		150000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.97	kN	No		
HEP :	25.0 %	25.93	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	21.16	kN	Yes 15	Times	
Ref :		20.74	kN			
LCP :	2.0 %	20.33	kN	Yes 15	Times	
LEP :	25.0 %	15.56	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	14.52	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.34	kN	Min :	3.22	kN	Punch NO.;	26
SD :	1.70	%	Max :	3.54	kN	Punch NO.;	40
Mean Main Pressure :	20.62	kN	Min :	19.15	kN	Punch NO.;	43
SD :	3.60	%	Max :	22.61	kN	Punch NO.;	53
Filling Depth :	Increase ; 15	Times	Decrease ; 10	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.70	mm	Main Thickness ;	4.71	mm
Filling Depth :	11.47	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.792	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.43	kN		
	Max ;	0.66	kN	Max Punch ;	5
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	19
Ejection Force :	Average ;	1.03	kN		
	Max ;	1.33	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	50018	Tablets			
A.W.C Counter :	47991	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	47991 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 800MG STIU2D00
User ID :	sj97904	Batch NO. :	IUM2500880
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 53 Sec
Total Counter :	50018	Total Running Time :	2122 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	30	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		150000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.43	kN	No		
HEP :	25.0 %	27.34	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	22.31	kN	Yes 20	Times	
Ref :		21.87	kN			
LCP :	2.0 %	21.43	kN	Yes 20	Times	
LEP :	25.0 %	16.40	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	15.31	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.60	kN	Min :	3.45	kN	Punch NO.;	28
SD :	1.90	%	Max :	3.78	kN	Punch NO.;	38
Mean Main Pressure :	22.15	kN	Min :	20.61	kN	Punch NO.;	15
SD :	3.50	%	Max :	24.72	kN	Punch NO.;	53
Filling Depth :	Increase ;	35	Times	Decrease ;	31	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.85	mm	Main Thickness ;	4.86	mm
Filling Depth :	11.50	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.792	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.43	kN		
	Max ;	0.66	kN	Max Punch ;	5
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	19
Ejection Force :	Average ;	1.03	kN		
	Max ;	1.33	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	50018	Tablets			
A.W.C Counter :	47991	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	47991 (100.0%)	Tablets			