

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 800MG STIU2D00
User ID :	ps99585	Batch NO. :	IUM2500880
Print Interval :	50000 Tablets	Running Time :	01 Hour 33 Min 37 Sec
Total Counter :	147192	Total Running Time :	2123 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	30	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		150000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.97	kN	No		
HEP :	25.0 %	25.93	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	21.16	kN	Yes 15	Times	
Ref :		20.74	kN			
LCP :	2.0 %	20.33	kN	Yes 15	Times	
LEP :	25.0 %	15.56	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	14.52	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.18	kN	Min :	3.05	kN	Punch NO.;	19
SD :	2.60	%	Max :	3.39	kN	Punch NO.;	31
Mean Main Pressure :	19.14	kN	Min :	17.51	kN	Punch NO.;	3
SD :	4.20	%	Max :	21.03	kN	Punch NO.;	10
Filling Depth :	Increase ; 66	Times	Decrease ; 45	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.70	mm	Main Thickness ;	4.71	mm
Filling Depth :	12.56	mm	Current Cam :	Cam D 12.5-18mm	
Main Air pressure :	0.815	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.52	kN		
	Max ;	0.81	kN	Max Punch ;	31
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.17	kN	Max Punch ;	50
Ejection Force :	Average ;	1.03	kN		
	Max ;	1.20	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	147192	Tablets		
A.W.C Counter :	144709	Tablets		
HEP :	340 (0.2%)	Tablets	LEP :	79 (0.1%) Tablets
GOOD :	144290 (99.7%)	Tablets		

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 800MG STIU2D00
User ID :	ps99585	Batch NO. :	IUM2500880
Print Interval :	50000 Tablets	Running Time :	01 Hour 33 Min 37 Sec
Total Counter :	147192	Total Running Time :	2123 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	30	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		150000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.43	kN	No		
HEP :	25.0 %	27.34	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	22.31	kN	Yes 20	Times	
Ref :		21.87	kN			
LCP :	2.0 %	21.43	kN	Yes 20	Times	
LEP :	25.0 %	16.40	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	15.31	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.24	kN	Min :	3.15	kN	Punch NO.;	46
SD :	1.60	%	Max :	3.41	kN	Punch NO.;	3
Mean Main Pressure :	17.53	kN	Min :	16.20	kN	Punch NO.;	43
SD :	3.00	%	Max :	18.57	kN	Punch NO.;	11
Filling Depth :	Increase ;	107	Times	Decrease ;	113	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.85	mm	Main Thickness ;	4.86	mm
Filling Depth :	11.57	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.815	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.54	kN		
	Max ;	0.79	kN	Max Punch ;	31
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.17	kN	Max Punch ;	50
Ejection Force :	Average ;	1.03	kN		
	Max ;	1.20	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	147192	Tablets			
A.W.C Counter :	144709	Tablets			
HEP :	340 (0.2%)	Tablets	LEP :	79 (0.1%)	Tablets
GOOD :	144290 (99.7%)	Tablets			