

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 800MG STIU2D00
User ID :	sj97904	Batch NO. :	IUM2500980
Print Interval :	50000 Tablets	Running Time :	01 Hour 03 Min 42 Sec
Total Counter :	100018	Total Running Time :	2124 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	30	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		150000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.26	kN	No		
HEP :	25.0 %	27.18	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	22.17	kN	Yes 15	Times	
Ref :		21.74	kN			
LCP :	2.0 %	21.31	kN	Yes 15	Times	
LEP :	25.0 %	16.31	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	15.22	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.47	kN	Min :	3.37	kN	Punch NO.;	17
SD :	1.80	%	Max :	3.65	kN	Punch NO.;	3
Mean Main Pressure :	21.53	kN	Min :	20.32	kN	Punch NO.;	41
SD :	3.10	%	Max :	23.20	kN	Punch NO.;	23
Filling Depth :	Increase ; 85	Times	Decrease ; 84	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.70	mm	Main Thickness ;	4.71	mm
Filling Depth :	11.38	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.713	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.45	kN		
	Max ;	0.66	kN	Max Punch ;	31
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.19	kN	Max Punch ;	42
Ejection Force :	Average ;	1.22	kN		
	Max ;	1.48	kN	Max Punch ;	47

Tablet Data (N/A)

Total Counter :	100018	Tablets			
A.W.C Counter :	98021	Tablets			
HEP :	217 (0.2%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	97803 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 800MG STIU2D00
User ID :	sj97904	Batch NO. :	IUM2500980
Print Interval :	50000 Tablets	Running Time :	01 Hour 03 Min 42 Sec
Total Counter :	100018	Total Running Time :	2124 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	30	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		150000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.72	kN	No		
HEP :	25.0 %	28.58	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	23.32	kN	Yes 20	Times	
Ref :		22.86	kN			
LCP :	2.0 %	22.41	kN	Yes 20	Times	
LEP :	25.0 %	17.15	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	16.00	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.68	kN	Min :	3.53	kN	Punch NO.;	14
SD :	1.90	%	Max :	3.87	kN	Punch NO.;	42
Mean Main Pressure :	23.51	kN	Min :	22.04	kN	Punch NO.;	33
SD :	3.20	%	Max :	25.54	kN	Punch NO.;	51
Filling Depth :	Increase ;	175	Times	Decrease ;	181	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.85	mm	Main Thickness ;	4.86	mm
Filling Depth :	11.65	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.713	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.43	kN		
	Max ;	0.63	kN	Max Punch ;	31
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.19	kN	Max Punch ;	42
Ejection Force :	Average ;	1.22	kN		
	Max ;	1.48	kN	Max Punch ;	47

Tablet Data (N/A)

Total Counter :	100018	Tablets			
A.W.C Counter :	98021	Tablets			
HEP :	217 (0.2%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	97803 (99.8%)	Tablets			