

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 800MG STIU2D00
User ID :	rp98927	Batch NO. :	IUM2501080
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 50 Sec
Total Counter :	50010	Total Running Time :	2125 Hour 33 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	30	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		150000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.26	kN	No		
HEP :	25.0 %	27.18	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	22.17	kN	Yes 15	Times	
Ref :		21.74	kN			
LCP :	2.0 %	21.31	kN	Yes 15	Times	
LEP :	25.0 %	16.31	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	15.22	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.56	kN	Min :	3.47	kN	Punch NO.;	14
SD :	1.20	%	Max :	3.65	kN	Punch NO.;	3
Mean Main Pressure :	21.97	kN	Min :	20.59	kN	Punch NO.;	41
SD :	3.00	%	Max :	23.41	kN	Punch NO.;	16
Filling Depth :	Increase ;	110	Times	Decrease ;	107	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.70	mm	Main Thickness ;	4.71	mm
Filling Depth :	11.44	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.799	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.35	kN		
	Max ;	0.48	kN	Max Punch ;	51
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.23	kN	Max Punch ;	4
Ejection Force :	Average ;	1.30	kN		
	Max ;	1.47	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	50010	Tablets			
A.W.C Counter :	47629	Tablets			
HEP :	79 (0.2%)	Tablets	LEP :	23 (0.0%)	Tablets
GOOD :	47527 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 800MG STIU2D00
User ID :	rp98927	Batch NO. :	IUM2501080
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 50 Sec
Total Counter :	50010	Total Running Time :	2125 Hour 33 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	182	%	Manual ;	30	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		150000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.72	kN	No		
HEP :	25.0 %	28.58	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	23.32	kN	Yes 20	Times	
Ref :		22.86	kN			
LCP :	2.0 %	22.41	kN	Yes 20	Times	
LEP :	25.0 %	17.15	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	16.00	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.73	kN	Min :	3.61	kN	Punch NO.;	14
SD :	1.70	%	Max :	3.89	kN	Punch NO.;	3
Mean Main Pressure :	23.13	kN	Min :	21.71	kN	Punch NO.;	43
SD :	3.40	%	Max :	25.19	kN	Punch NO.;	53
Filling Depth :	Increase ;	253	Times	Decrease ;	243	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.85	mm	Main Thickness ;	4.86	mm
Filling Depth :	11.65	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.799	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.35	kN		
	Max ;	0.48	kN	Max Punch ;	51
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.23	kN	Max Punch ;	4
Ejection Force :	Average ;	1.30	kN		
	Max ;	1.47	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	50010	Tablets			
A.W.C Counter :	47629	Tablets			
HEP :	79 (0.2%)	Tablets	LEP :	23 (0.0%)	Tablets
GOOD :	47527 (99.8%)	Tablets			