

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000 MG,STYQ1A00
User ID :	vg96371	Batch NO. :	YQM2501910
Print Interval :	50000 Tablets	Running Time :	02 Hour 36 Min 04 Sec
Total Counter :	250088	Total Running Time :	2129 Hour 12 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2250000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.52	kN	No		
HEP :	25.0 %	25.50	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	20.81	kN	Yes 15	Times	
Ref :		20.40	kN			
LCP :	2.0 %	19.99	kN	Yes 15	Times	
LEP :	25.0 %	15.30	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	14.28	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.80	kN	Min :	3.63	kN	Punch NO.;	25
SD :	1.60	%	Max :	3.96	kN	Punch NO.;	46
Mean Main Pressure :	20.74	kN	Min :	19.80	kN	Punch NO.;	25
SD :	2.10	%	Max :	21.90	kN	Punch NO.;	1
Filling Depth :	Increase ; 48	Times	Decrease ; 62	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.20	mm	Pre Thickness ;	5.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.45	mm	Main Thickness ;	4.45	mm
Filling Depth :	10.41	mm	Current Cam :	Cam C	
Main Air pressure :	0.795	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.29	kN		
	Max ;	0.44	kN	Max Punch ;	27
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	21
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	250088	Tablets			
A.W.C Counter :	246398	Tablets			
HEP :	4 (0.0%)	Tablets	LEP :	73 (0.0%)	Tablets
GOOD :	246321 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000 MG,STYQ1A00
User ID :	vg96371	Batch NO. :	YQM2501910
Print Interval :	50000 Tablets	Running Time :	02 Hour 36 Min 04 Sec
Total Counter :	250088	Total Running Time :	2129 Hour 12 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2250000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.05	kN	No		
HEP :	25.0 %	26.01	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	21.22	kN	Yes 20	Times	
Ref :		20.81	kN			
LCP :	2.0 %	20.39	kN	Yes 20	Times	
LEP :	25.0 %	15.60	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	14.56	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.67	kN	Min :	3.49	kN	Punch NO.;	19
		2.50	%	Max :	3.98	kN	Punch NO.;	46
Mean Main Pressure :	SD :	21.06	kN	Min :	19.60	kN	Punch NO.;	19
		3.30	%	Max :	23.28	kN	Punch NO.;	46
Filling Depth :	Increase ;	57	Times	Decrease ;	57	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.20	mm	Pre Thickness ;	5.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.60	mm	Main Thickness ;	4.60	mm
Filling Depth :	10.08	mm	Current Cam :	Cam C	
Main Air pressure :	0.795	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.29	kN		
	Max ;	0.44	kN	Max Punch ;	27
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	21
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	250088	Tablets			
A.W.C Counter :	246398	Tablets			
HEP :	4 (0.0%)	Tablets	LEP :	73 (0.0%)	Tablets
GOOD :	246321 (100.0%)	Tablets			