

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000mg STYQ1A00
User ID :	pb97604	Batch NO. :	YQM2502110
Print Interval :	50000 Tablets	Running Time :	00 Hour 08 Min 21 Sec
Total Counter :	13056	Total Running Time :	2146 Hour 58 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	146	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.52	kN	No		
HEP :	25.0 %	26.46	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	21.59	kN	Yes 15	Times	
Ref :		21.17	kN			
LCP :	2.0 %	20.75	kN	Yes 15	Times	
LEP :	25.0 %	15.88	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	14.82	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.31	kN	Min :	3.12	kN	Punch NO.;	17
		1.70	%	Max :	3.41	kN	Punch NO.;	15
Mean Main Pressure :		21.42	kN	Min :	20.20	kN	Punch NO.;	5
	SD :	2.40	%	Max :	22.70	kN	Punch NO.;	32
Filling Depth :	Increase ;	8	Times	Decrease ;	6	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.30	mm	Pre Thickness ;	5.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.30	mm	Main Thickness ;	4.31	mm
Filling Depth :	10.63	mm	Current Cam :	Cam C	
Main Air pressure :	0.752	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.17	kN	Max Punch ;	23
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	46
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.11	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	13056	Tablets			
A.W.C Counter :	10844	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	10844 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000mg STYQ1A00
User ID :	pb97604	Batch NO. :	YQM2502110
Print Interval :	50000 Tablets	Running Time :	00 Hour 08 Min 21 Sec
Total Counter :	13056	Total Running Time :	2146 Hour 58 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	135	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.58	kN	No		
HEP :	25.0 %	28.44	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	23.21	kN	Yes 20	Times	
Ref :		22.75	kN			
LCP :	2.0 %	22.30	kN	Yes 20	Times	
LEP :	25.0 %	17.07	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	15.93	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.41	kN	Min :	3.25	kN	Punch NO.;	17
SD :	1.50	%	Max :	3.56	kN	Punch NO.;	32
Mean Main Pressure :	22.47	kN	Min :	21.33	kN	Punch NO.;	49
SD :	2.60	%	Max :	23.99	kN	Punch NO.;	32
Filling Depth :	Increase ;	12	Times	Decrease ;	1	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.30	mm	Pre Thickness ;	5.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.40	mm	Main Thickness ;	4.41	mm
Filling Depth :	10.21	mm	Current Cam :	Cam C	
Main Air pressure :	0.752	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.17	kN	Max Punch ;	23
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	46
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.09	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	13056	Tablets			
A.W.C Counter :	10844	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	10844 (100.0%)	Tablets			