

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000mg STYQ1A00
User ID :	pb97604	Batch NO. :	YQM2502110
Print Interval :	50000 Tablets	Running Time :	05 Hour 33 Min 29 Sec
Total Counter :	550126	Total Running Time :	2152 Hour 24 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	147	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.95	kN	No		
HEP :	25.0 %	23.99	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	19.58	kN	Yes 15	Times	
Ref :		19.19	kN			
LCP :	2.0 %	18.81	kN	Yes 15	Times	
LEP :	25.0 %	14.39	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	13.44	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.34	kN	Min :	3.19	kN	Punch NO.;	35
SD :	1.70	%	Max :	3.49	kN	Punch NO.;	12
Mean Main Pressure :	19.64	kN	Min :	18.64	kN	Punch NO.;	5
SD :	2.10	%	Max :	20.94	kN	Punch NO.;	12
Filling Depth :	Increase ; 124	Times	Decrease ;	105	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.30	mm	Pre Thickness ;	5.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.39	mm	Main Thickness ;	4.40	mm
Filling Depth :	10.68	mm	Current Cam :	Cam C	
Main Air pressure :	0.790	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	46
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	550126	Tablets			
A.W.C Counter :	547741	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	547741 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000mg STYQ1A00
User ID :	pb97604	Batch NO. :	YQM2502110
Print Interval :	50000 Tablets	Running Time :	05 Hour 33 Min 29 Sec
Total Counter :	550126	Total Running Time :	2152 Hour 24 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	148	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.43	kN	No		
HEP :	25.0 %	24.45	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	19.95	kN	Yes 20	Times	
Ref :		19.56	kN			
LCP :	2.0 %	19.17	kN	Yes 20	Times	
LEP :	25.0 %	14.67	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	13.69	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.44	kN	Min :	3.25	kN	Punch NO.;	35
SD :	2.40	%	Max :	3.60	kN	Punch NO.;	12
Mean Main Pressure :	19.61	kN	Min :	18.00	kN	Punch NO.;	35
SD :	3.60	%	Max :	21.07	kN	Punch NO.;	50
Filling Depth :	Increase ;	116	Times	Decrease ;	100	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.30	mm	Pre Thickness ;	5.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.55	mm	Main Thickness ;	4.56	mm
Filling Depth :	10.28	mm	Current Cam :	Cam C	
Main Air pressure :	0.790	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	46
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	550126	Tablets			
A.W.C Counter :	547741	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	547741 (100.0%)	Tablets			