

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000mg STYQ1A00
User ID :	pn98247	Batch NO. :	YQM2502110
Print Interval :	50000 Tablets	Running Time :	16 Hour 24 Min 59 Sec
Total Counter :	1650434	Total Running Time :	2163 Hour 17 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	147	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		200	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		90	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.97	kN	No		
HEP :	25.0 %	24.97	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	20.38	kN	Yes 15	Times	
Ref :		19.98	kN			
LCP :	2.0 %	19.58	kN	Yes 15	Times	
LEP :	25.0 %	14.98	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	13.98	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.31	kN	Min :	3.14	kN	Punch NO.;	17
		1.80	%	Max :	3.50	kN	Punch NO.;	12
Mean Main Pressure :		20.28	kN	Min :	19.01	kN	Punch NO.;	35
	SD :	2.40	%	Max :	21.29	kN	Punch NO.;	1
Filling Depth :	Increase ;	407	Times	Decrease ;	385	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.30	mm	Pre Thickness ;	5.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.39	mm	Main Thickness ;	4.40	mm
Filling Depth :	10.76	mm	Current Cam :	Cam C	
Main Air pressure :	0.798	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	161	Min			
Lower Punch Remain Time (S2):	63	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	33
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.11	kN	Max Punch ;	21

Tablet Data (N/A)

Total Counter :	1650434	Tablets			
A.W.C Counter :	1647737	Tablets			
HEP :	0 (0%)	Tablets	LEP :	2619 (0.2%)	Tablets
GOOD :	1645118 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : pn98247 Print Interval : 50000 Tablets Total Counter : 1650434 Station : Station 2	Product Name : MET 1000mg STYQ1A00 Batch NO. : YQM2502110 Running Time : 16 Hour 24 Min 59 Sec Total Running Time : 2163 Hour 17 Min
---	---

Setting Value

Feeder :	Auto ;	148	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		2250000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		200	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		90	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.36	kN	No		
HEP :	25.0 %	25.34	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	20.68	kN	Yes 20	Times	
Ref :		20.27	kN			
LCP :	2.0 %	19.87	kN	Yes 20	Times	
LEP :	25.0 %	15.21	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	14.19	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.46	kN	Min :	3.27	kN	Punch NO.;	35
		2.30	%	Max :	3.66	kN	Punch NO.;	1
Mean Main Pressure :		20.28	kN	Min :	18.81	kN	Punch NO.;	35
	SD :	3.20	%	Max :	21.71	kN	Punch NO.;	1
Filling Depth :	Increase ;	228	Times	Decrease ;	223	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.30	mm	Pre Thickness ;	5.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.55	mm	Main Thickness ;	4.56	mm
Filling Depth :	10.28	mm	Current Cam :	Cam C	
Main Air pressure :	0.798	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	161	Min			
Lower Punch Remain Time (S2):	63	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	33
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.12	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	1650434	Tablets			
A.W.C Counter :	1647737	Tablets			
HEP :	0 (0%)	Tablets	LEP :	2619 (0.2%)	Tablets
GOOD :	1645118 (99.8%)	Tablets			