

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000mg STYQ1A00
User ID :	pb97604	Batch NO. :	YQM2502110
Print Interval :	50000 Tablets	Running Time :	20 Hour 51 Min 27 Sec
Total Counter :	2100566	Total Running Time :	2167 Hour 44 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	147	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		200	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		90	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.59	kN	No		
HEP :	25.0 %	24.61	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	20.08	kN	Yes 15	Times	
Ref :		19.69	kN			
LCP :	2.0 %	19.29	kN	Yes 15	Times	
LEP :	25.0 %	14.77	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	13.78	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.31	kN	Min :	3.18	kN	Punch NO.;	17
SD :	1.50	%	Max :	3.40	kN	Punch NO.;	12
Mean Main Pressure :	19.69	kN	Min :	18.30	kN	Punch NO.;	29
SD :	2.10	%	Max :	20.53	kN	Punch NO.;	45
Filling Depth :	Increase ;	498	Times	Decrease ;	490	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.29	mm	Pre Thickness ;	5.30	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.41	mm	Main Thickness ;	4.42	mm
Filling Depth :	10.36	mm	Current Cam :	Cam C	
Main Air pressure :	0.807	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	96	Min			
Lower Punch Remain Time (S2):	68	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	36
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.14	kN	Max Punch ;	32

Tablet Data (N/A)

Total Counter :	2100566	Tablets			
A.W.C Counter :	2097584	Tablets			
HEP :	0 (0%)	Tablets	LEP :	2619 (0.1%)	Tablets
GOOD :	2094965 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : pb97604 Print Interval : 50000 Tablets Total Counter : 2100566 Station : Station 2	Product Name : MET 1000mg STYQ1A00 Batch NO. : YQM2502110 Running Time : 20 Hour 51 Min 27 Sec Total Running Time : 2167 Hour 44 Min
---	---

Setting Value

Feeder :	Auto ;	148	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		2250000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		200	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		90	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.21	kN	No		
HEP :	25.0 %	24.24	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	19.78	kN	Yes 20	Times	
Ref :		19.39	kN			
LCP :	2.0 %	19.00	kN	Yes 20	Times	
LEP :	25.0 %	14.54	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	13.57	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.47	kN	Min :	3.26	kN	Punch NO.;	17
		2.40	%	Max :	3.66	kN	Punch NO.;	12
Mean Main Pressure :		19.55	kN	Min :	18.27	kN	Punch NO.;	35
	SD :	3.20	%	Max :	20.94	kN	Punch NO.;	12
Filling Depth :	Increase ;	309	Times	Decrease ;	303	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.29	mm	Pre Thickness ;	5.30	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.58	mm	Main Thickness ;	4.59	mm
Filling Depth :	10.23	mm	Current Cam :	Cam C	
Main Air pressure :	0.807	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	96	Min			
Lower Punch Remain Time (S2):	68	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	36
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.14	kN	Max Punch ;	32

Tablet Data (N/A)

Total Counter :	2100566	Tablets			
A.W.C Counter :	2097584	Tablets			
HEP :	0 (0%)	Tablets	LEP :	2619 (0.1%)	Tablets
GOOD :	2094965 (99.9%)	Tablets			