

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000mg STYQ1A00
User ID :	pb97604	Batch NO. :	YQM2502110
Print Interval :	50000 Tablets	Running Time :	22 Hour 18 Min 32 Sec
Total Counter :	2247718	Total Running Time :	2169 Hour 12 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	147	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		200	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		90	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.59	kN	No		
HEP :	25.0 %	24.61	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	20.08	kN	Yes 15	Times	
Ref :		19.69	kN			
LCP :	2.0 %	19.29	kN	Yes 15	Times	
LEP :	25.0 %	14.77	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	13.78	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.32	kN	Min :	3.13	kN	Punch NO.;	17
		1.70	%	Max :	3.45	kN	Punch NO.;	15
Mean Main Pressure :		19.68	kN	Min :	18.62	kN	Punch NO.;	31
	SD :	2.10	%	Max :	20.55	kN	Punch NO.;	40
Filling Depth :	Increase ;	536	Times	Decrease ;	518	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.29	mm	Pre Thickness ;	5.30	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.41	mm	Main Thickness ;	4.42	mm
Filling Depth :	10.47	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	71	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	33
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	40

Tablet Data (N/A)

Total Counter :	2247718	Tablets			
A.W.C Counter :	2244712	Tablets			
HEP :	0 (0%)	Tablets	LEP :	2619 (0.1%)	Tablets
GOOD :	2242093 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000mg STYQ1A00
User ID :	pb97604	Batch NO. :	YQM2502110
Print Interval :	50000 Tablets	Running Time :	22 Hour 18 Min 32 Sec
Total Counter :	2247718	Total Running Time :	2169 Hour 12 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	148	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		200	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		90	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.21	kN	No		
HEP :	25.0 %	24.24	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	19.78	kN	Yes 20	Times	
Ref :		19.39	kN			
LCP :	2.0 %	19.00	kN	Yes 20	Times	
LEP :	25.0 %	14.54	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	13.57	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.43	kN	Min :	3.29	kN	Punch NO.;	7
SD :	2.00	%	Max :	3.59	kN	Punch NO.;	52
Mean Main Pressure :	19.35	kN	Min :	18.02	kN	Punch NO.;	23
SD :	2.90	%	Max :	20.87	kN	Punch NO.;	52
Filling Depth :	Increase ;	326	Times	Decrease ;	317	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.29	mm	Pre Thickness ;	5.30	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.58	mm	Main Thickness ;	4.59	mm
Filling Depth :	10.32	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	71	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	33
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	40

Tablet Data (N/A)

Total Counter :	2247718	Tablets			
A.W.C Counter :	2244712	Tablets			
HEP :	0 (0%)	Tablets	LEP :	2619 (0.1%)	Tablets
GOOD :	2242093 (99.9%)	Tablets			