

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400MG STIU2B00
User ID :	rp98927	Batch NO. :	IUM2500740
Print Interval :	50000 Tablets	Running Time :	00 Hour 07 Min 33 Sec
Total Counter :	14866	Total Running Time :	2191 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	147	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.40	kN	No		
HEP :	25.0 %	26.34	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	21.50	kN	Yes 15	Times	
Ref :		21.08	kN			
LCP :	2.0 %	20.65	kN	Yes 15	Times	
LEP :	25.0 %	15.81	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	14.75	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.63	kN	Min :	2.55	kN	Punch NO.;	13
		1.30	%	Max :	2.70	kN	Punch NO.;	25
Mean Main Pressure :	SD :	20.89	kN	Min :	19.72	kN	Punch NO.;	31
		2.40	%	Max :	21.99	kN	Punch NO.;	51
Filling Depth :	Increase ;	8	Times	Decrease ;	0	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	7.60	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	16
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	14866	Tablets			
A.W.C Counter :	11625	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	11625 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400MG STIU2B00
User ID :	rp98927	Batch NO. :	IUM2500740
Print Interval :	50000 Tablets	Running Time :	00 Hour 07 Min 33 Sec
Total Counter :	14866	Total Running Time :	2191 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	148	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.88	kN	No		
HEP :	25.0 %	28.73	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	23.44	kN	Yes 20	Times	
Ref :		22.99	kN			
LCP :	2.0 %	22.53	kN	Yes 20	Times	
LEP :	25.0 %	17.24	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	16.09	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.81	kN	Min :	2.73	kN	Punch NO.;	17
SD :	1.70	%	Max :	2.94	kN	Punch NO.;	1
Mean Main Pressure :	23.25	kN	Min :	21.73	kN	Punch NO.;	36
SD :	3.50	%	Max :	25.07	kN	Punch NO.;	14
Filling Depth :	Increase ; 7	Times	Decrease ; 4	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	7.72	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	16
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	14866	Tablets			
A.W.C Counter :	11678	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	11678 (100.0%)	Tablets			