

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500740
Print Interval :	50000 Tablets	Running Time :	04 Hour 22 Min 41 Sec
Total Counter :	554908	Total Running Time :	2195 Hour 46 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	201	%	Manual ;	57	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.84	kN	No		
HEP :	25.0 %	26.77	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	21.85	kN	Yes 15	Times	
Ref :		21.42	kN			
LCP :	2.0 %	20.99	kN	Yes 15	Times	
LEP :	25.0 %	16.06	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	14.99	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.54	kN	Min :	2.46	kN	Punch NO.;	33
SD :	1.30	%	Max :	2.62	kN	Punch NO.;	27
Mean Main Pressure :	21.36	kN	Min :	20.23	kN	Punch NO.;	29
SD :	2.10	%	Max :	22.23	kN	Punch NO.;	27
Filling Depth :	Increase ; 161	Times	Decrease ;	110	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.30	mm	Pre Thickness ;	3.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	7.24	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.799	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	68	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.27	kN	Max Punch ;	11
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	554908	Tablets			
A.W.C Counter :	546912	Tablets			
HEP :	862 (0.2%)	Tablets	LEP :	73 (0.0%)	Tablets
GOOD :	545977 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500740
Print Interval :	50000 Tablets	Running Time :	04 Hour 22 Min 41 Sec
Total Counter :	554908	Total Running Time :	2195 Hour 46 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	224	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.54	kN	No		
HEP :	25.0 %	25.52	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	20.82	kN	Yes 20	Times	
Ref :		20.41	kN			
LCP :	2.0 %	20.01	kN	Yes 20	Times	
LEP :	25.0 %	15.31	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	14.29	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.83	kN	Min :	2.74	kN	Punch NO.;	9
SD :	1.30	%	Max :	2.90	kN	Punch NO.;	40
Mean Main Pressure :	20.81	kN	Min :	19.73	kN	Punch NO.;	11
SD :	2.80	%	Max :	22.33	kN	Punch NO.;	40
Filling Depth :	Increase ; 124	Times	Decrease ;	122	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	45	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.53	mm
Filling Depth :	7.33	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	68	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.27	kN	Max Punch ;	11
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	554908	Tablets			
A.W.C Counter :	546912	Tablets			
HEP :	862 (0.2%)	Tablets	LEP :	73 (0.0%)	Tablets
GOOD :	545977 (99.8%)	Tablets			