

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400MG STIU2B00
User ID :	sj97904	Batch NO. :	IUM2500740
Print Interval :	50000 Tablets	Running Time :	13 Hour 25 Min 37 Sec
Total Counter :	1705298	Total Running Time :	2204 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	201	%	Manual ;	57	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		2025000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.25	kN	No		
HEP :	25.0 %	27.16	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	22.17	kN	Yes 15	Times	
Ref :		21.73	kN			
LCP :	2.0 %	21.30	kN	Yes 15	Times	
LEP :	25.0 %	16.30	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	15.21	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.44	kN	Min :	2.37	kN	Punch NO.;	14
SD :	1.50	%	Max :	2.52	kN	Punch NO.;	42
Mean Main Pressure :	21.93	kN	Min :	20.63	kN	Punch NO.;	36
SD :	2.20	%	Max :	22.97	kN	Punch NO.;	48
Filling Depth :	Increase ; 306	Times	Decrease ;	230	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.30	mm	Pre Thickness ;	3.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	7.62	mm	Current Cam :	Cam C	
Main Air pressure :	0.789	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.34	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1705298	Tablets			
A.W.C Counter :	1695758	Tablets			
HEP :	1060 (0.1%)	Tablets	LEP :	134 (0.0%)	Tablets
GOOD :	1694564 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400MG STIU2B00
User ID :	sj97904	Batch NO. :	IUM2500740
Print Interval :	50000 Tablets	Running Time :	13 Hour 25 Min 37 Sec
Total Counter :	1705298	Total Running Time :	2204 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.47	kN	No		
HEP :	25.0 %	26.41	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	21.55	kN	Yes 20	Times	
Ref :		21.13	kN			
LCP :	2.0 %	20.71	kN	Yes 20	Times	
LEP :	25.0 %	15.85	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	14.79	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.74	kN	Min :	2.67	kN	Punch NO.;	10
SD :	1.10	%	Max :	2.81	kN	Punch NO.;	43
Mean Main Pressure :	21.11	kN	Min :	19.86	kN	Punch NO.;	11
SD :	2.50	%	Max :	22.13	kN	Punch NO.;	22
Filling Depth :	Increase ;	225	Times	Decrease ;	228	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.53	mm
Filling Depth :	7.49	mm	Current Cam :	Cam C	
Main Air pressure :	0.789	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.34	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1705298	Tablets			
A.W.C Counter :	1695758	Tablets			
HEP :	1060 (0.1%)	Tablets	LEP :	134 (0.0%)	Tablets
GOOD :	1694564 (99.9%)	Tablets			