

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400MG STIU2B00
User ID :	sj97904	Batch NO. :	IUM2500740
Print Interval :	50000 Tablets	Running Time :	15 Hour 47 Min 14 Sec
Total Counter :	2005444	Total Running Time :	2207 Hour 13 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	212	%	Manual ;	57	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	30.00	kN	No		
HEP :	25.0 %	28.85	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	23.54	kN	Yes 15	Times	
Ref :		23.08	kN			
LCP :	2.0 %	22.62	kN	Yes 15	Times	
LEP :	25.0 %	17.31	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	16.15	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.48	kN	Min :	2.38	kN	Punch NO.;	34
SD :	1.60	%	Max :	2.59	kN	Punch NO.;	42
Mean Main Pressure :	22.35	kN	Min :	20.98	kN	Punch NO.;	17
SD :	2.20	%	Max :	23.39	kN	Punch NO.;	8
Filling Depth :	Increase ;	378	Times	Decrease ;	320	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	42	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.30	mm	Pre Thickness ;	3.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.42	mm	Main Thickness ;	2.42	mm
Filling Depth :	7.62	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.793	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.42	kN	Max Punch ;	31
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	32

Tablet Data (N/A)

Total Counter :	2005444	Tablets			
A.W.C Counter :	1995799	Tablets			
HEP :	1061 (0.1%)	Tablets	LEP :	134 (0.0%)	Tablets
GOOD :	1994604 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400MG STIU2B00
User ID :	sj97904	Batch NO. :	IUM2500740
Print Interval :	50000 Tablets	Running Time :	15 Hour 47 Min 14 Sec
Total Counter :	2005444	Total Running Time :	2207 Hour 13 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.31	kN	No		
HEP :	25.0 %	27.22	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	22.21	kN	Yes 20	Times	
Ref :		21.78	kN			
LCP :	2.0 %	21.34	kN	Yes 20	Times	
LEP :	25.0 %	16.33	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	15.25	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.77	kN	Min :	2.70	kN	Punch NO.;	34
		1.10	%	Max :	2.85	kN	Punch NO.;	4
Mean Main Pressure :		21.61	kN	Min :	20.69	kN	Punch NO.;	40
	SD :	2.40	%	Max :	22.96	kN	Punch NO.;	14
Filling Depth :	Increase ;	256	Times	Decrease ;	278	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.53	mm
Filling Depth :	7.52	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.793	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.42	kN	Max Punch ;	31
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	32

Tablet Data (N/A)

Total Counter :	2005444	Tablets			
A.W.C Counter :	1995799	Tablets			
HEP :	1061 (0.1%)	Tablets	LEP :	134 (0.0%)	Tablets
GOOD :	1994604 (99.9%)	Tablets			