

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	OXAZEPAM 10 STXZ3B00
User ID :	rp98927	Batch NO. :	XZM2500610
Print Interval :	50000 Tablets	Running Time :	17 Hour 50 Min 33 Sec
Total Counter :	2776190	Total Running Time :	2227 Hour 20 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	5.79	kN	No		
HEP :	20.0 %	5.56	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	4.72	kN	Yes 15	Times	
Ref :		4.63	kN			
LCP :	2.0 %	4.54	kN	Yes 15	Times	
LEP :	20.0 %	3.70	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	3.47	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.24	kN	Min :	2.21	kN	Punch NO.;	28
SD :	0.80	%	Max :	2.29	kN	Punch NO.;	64
Mean Main Pressure :	4.60	kN	Min :	4.52	kN	Punch NO.;	13
SD :	0.80	%	Max :	4.67	kN	Punch NO.;	64
Filling Depth :	Increase ; 9	Times	Decrease ;	0	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.99	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.80	mm	Main Thickness ;	2.81	mm
Filling Depth :	7.24	mm	Current Cam :	Cam B	
Main Air pressure :	0.808	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.28	kN		
	Max ;	0.31	kN	Max Punch ;	2
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.08	kN	Max Punch ;	48
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	2776190	Tablets			
A.W.C Counter :	2773886	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2773885 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	OXAZEPAM 10 STXZ3B00
User ID :	rp98927	Batch NO. :	XZM2500610
Print Interval :	50000 Tablets	Running Time :	17 Hour 50 Min 33 Sec
Total Counter :	2776190	Total Running Time :	2227 Hour 20 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	6.35	kN	No		
HEP :	20.0 %	6.09	kN	Yes	15	Rotations
HCP :	2.0 %	5.18	kN	Yes	20	Times
Ref :		5.08	kN			
LCP :	2.0 %	4.98	kN	Yes	20	Times
LEP :	20.0 %	4.06	kN	Yes	15	Rotations
LSP :	25.0 %	3.81	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.22	kN	Min :	2.18	kN	Punch NO.;	41
SD :	0.70	%	Max :	2.25	kN	Punch NO.;	30
Mean Main Pressure :	5.15	kN	Min :	5.05	kN	Punch NO.;	52
SD :	0.80	%	Max :	5.26	kN	Punch NO.;	46
Filling Depth :	Increase ;	21	Times	Decrease ;	32	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.03	mm	Main Thickness ;	3.04	mm
Filling Depth :	7.59	mm	Current Cam :	Cam B	
Main Air pressure :	0.808	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.28	kN		
	Max ;	0.30	kN	Max Punch ;	25
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.08	kN	Max Punch ;	48
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	2776190	Tablets			
A.W.C Counter :	2773886	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2773885 (100.0%)	Tablets			