

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	OXAZEPAM 10 STXZ3B00
User ID :	sj97904	Batch NO. :	XZM2500610
Print Interval :	50000 Tablets	Running Time :	21 Hour 03 Min 00 Sec
Total Counter :	3276442	Total Running Time :	2230 Hour 33 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	5.79	kN	No		
HEP :	20.0 %	5.56	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	4.72	kN	Yes 15	Times	
Ref :		4.63	kN			
LCP :	2.0 %	4.54	kN	Yes 15	Times	
LEP :	20.0 %	3.70	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	3.47	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.23	kN	Min :	2.19	kN	Punch NO.;	20
SD :	0.80	%	Max :	2.26	kN	Punch NO.;	30
Mean Main Pressure :	4.59	kN	Min :	4.51	kN	Punch NO.;	28
SD :	0.70	%	Max :	4.67	kN	Punch NO.;	31
Filling Depth :	Increase ; 9	Times	Decrease ; 0	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.99	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.80	mm	Main Thickness ;	2.81	mm
Filling Depth :	7.69	mm	Current Cam :	Cam B	
Main Air pressure :	0.787	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	28	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.27	kN		
	Max ;	0.29	kN	Max Punch ;	63
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.08	kN	Max Punch ;	27
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	3276442	Tablets			
A.W.C Counter :	3273932	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	3273931 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	OXAZEPAM 10 STXZ3B00
User ID :	sj97904	Batch NO. :	XZM2500610
Print Interval :	50000 Tablets	Running Time :	21 Hour 03 Min 00 Sec
Total Counter :	3276442	Total Running Time :	2230 Hour 33 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	6.35	kN	No		
HEP :	20.0 %	6.09	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	5.18	kN	Yes 20	Times	
Ref :		5.08	kN			
LCP :	2.0 %	4.98	kN	Yes 20	Times	
LEP :	20.0 %	4.06	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	3.81	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.20	kN	Min :	2.15	kN	Punch NO.;	38
SD :	0.70	%	Max :	2.24	kN	Punch NO.;	46
Mean Main Pressure :	5.06	kN	Min :	4.99	kN	Punch NO.;	28
SD :	0.90	%	Max :	5.19	kN	Punch NO.;	46
Filling Depth :	Increase ;	22	Times	Decrease ;	35	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.03	mm	Main Thickness ;	3.04	mm
Filling Depth :	7.60	mm	Current Cam :	Cam B	
Main Air pressure :	0.787	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	28	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.27	kN		
	Max ;	0.29	kN	Max Punch ;	65
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.08	kN	Max Punch ;	27
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	3276442	Tablets			
A.W.C Counter :	3273932	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	3273931 (100.0%)	Tablets			