

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LER HCL20MG STDJ1B00
User ID :	pb97604	Batch NO. :	DJM2500520
Print Interval :	50000 Tablets	Running Time :	15 Hour 38 Min 44 Sec
Total Counter :	2176300	Total Running Time :	2270 Hour 9 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2550000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	12.87	kN	No		
HEP :	20.0 %	12.35	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	10.50	kN	Yes 15	Times	
Ref :		10.29	kN			
LCP :	2.0 %	10.09	kN	Yes 15	Times	
LEP :	20.0 %	8.23	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	7.72	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.42	kN	Min :	2.37	kN	Punch NO.;	46
SD :	1.30	%	Max :	2.49	kN	Punch NO.;	7
Mean Main Pressure :	10.40	kN	Min :	9.77	kN	Punch NO.;	41
SD :	3.00	%	Max :	11.06	kN	Punch NO.;	52
Filling Depth :	Increase ; 8	Times	Decrease ; 8	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.09	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.15	mm	Main Thickness ;	2.16	mm
Filling Depth :	5.77	mm	Current Cam :	Cam B	
Main Air pressure :	0.817	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.27	kN		
	Max ;	0.33	kN	Max Punch ;	32
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	21
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.12	kN	Max Punch ;	47

Tablet Data (N/A)

Total Counter :	2176300	Tablets			
A.W.C Counter :	2173211	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2173211 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LER HCL20MG STDJ1B00
User ID :	pb97604	Batch NO. :	DJM2500520
Print Interval :	50000 Tablets	Running Time :	15 Hour 38 Min 44 Sec
Total Counter :	2176300	Total Running Time :	2270 Hour 9 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2550000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	12.86	kN	No		
HEP :	20.0 %	12.34	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	10.49	kN	Yes 20	Times	
Ref :		10.29	kN			
LCP :	2.0 %	10.08	kN	Yes 20	Times	
LEP :	20.0 %	8.23	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	7.71	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.60	kN	Min :	2.54	kN	Punch NO.;	5
SD :	1.10	%	Max :	2.69	kN	Punch NO.;	29
Mean Main Pressure :	10.45	kN	Min :	9.93	kN	Punch NO.;	18
SD :	2.40	%	Max :	11.03	kN	Punch NO.;	10
Filling Depth :	Increase ;	3	Times	Decrease ;	7	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.08	mm	Pre Thickness ;	3.09	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.37	mm	Main Thickness ;	2.38	mm
Filling Depth :	6.02	mm	Current Cam :	Cam B	
Main Air pressure :	0.817	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.26	kN		
	Max ;	0.35	kN	Max Punch ;	32
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	21
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.12	kN	Max Punch ;	47

Tablet Data (N/A)

Total Counter :	2176300	Tablets			
A.W.C Counter :	2173211	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2173211 (100.0%)	Tablets			