

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	pb97604	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	00 Hour 08 Min 51 Sec
Total Counter :	19264	Total Running Time :	2272 Hour 44 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	32	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.23	kN	No		
HEP :	20.0 %	8.86	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	7.53	kN	Yes 15	Times	
Ref :		7.38	kN			
LCP :	2.0 %	7.23	kN	Yes 15	Times	
LEP :	20.0 %	5.90	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	5.54	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.88	kN	Min :	1.86	kN	Punch NO.;	42
SD :	0.50	%	Max :	1.91	kN	Punch NO.;	3
Mean Main Pressure :	7.49	kN	Min :	6.49	kN	Punch NO.;	54
SD :	6.00	%	Max :	8.61	kN	Punch NO.;	10
Filling Depth :	Increase ;	13	Times	Decrease ;	8	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.47	mm
Filling Depth :	4.04	mm	Current Cam :	Cam B	
Main Air pressure :	0.808	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	34	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.36	kN	Max Punch ;	50
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	38
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	22

Tablet Data (N/A)

Total Counter :	19264	Tablets			
A.W.C Counter :	9623	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	9 (0.1%)	Tablets
GOOD :	9612 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	pb97604	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	00 Hour 08 Min 51 Sec
Total Counter :	19264	Total Running Time :	2272 Hour 44 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	33	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.62	kN	No		
HEP :	20.0 %	9.24	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	7.85	kN	Yes 20	Times	
Ref :		7.70	kN			
LCP :	2.0 %	7.54	kN	Yes 20	Times	
LEP :	20.0 %	6.16	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	5.77	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.04	kN	Min :	2.01	kN	Punch NO.;	6
SD :	0.70	%	Max :	2.08	kN	Punch NO.;	12
Mean Main Pressure :	7.66	kN	Min :	6.54	kN	Punch NO.;	54
SD :	4.40	%	Max :	8.54	kN	Punch NO.;	2
Filling Depth :	Increase ; 2	Times	Decrease ; 1	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.67	mm
Filling Depth :	4.13	mm	Current Cam :	Cam B	
Main Air pressure :	0.808	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	34	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.36	kN	Max Punch ;	50
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	49
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	19264	Tablets			
A.W.C Counter :	9623	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	9 (0.1%)	Tablets
GOOD :	9612 (99.9%)	Tablets			