

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	pb97604	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	01 Hour 50 Min 48 Sec
Total Counter :	350152	Total Running Time :	2274 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	48	%	Manual ;	57	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		6400000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	10.97	kN	No		
HEP :	20.0 %	10.53	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	8.95	kN	Yes 15	Times	
Ref :		8.78	kN			
LCP :	2.0 %	8.60	kN	Yes 15	Times	
LEP :	20.0 %	7.02	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	6.58	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.82	kN	Min :	1.80	kN	Punch NO.;	18
SD :	0.60	%	Max :	1.85	kN	Punch NO.;	25
Mean Main Pressure :	8.87	kN	Min :	7.10	kN	Punch NO.;	46
SD :	6.30	%	Max :	10.15	kN	Punch NO.;	48
Filling Depth :	Increase ; 16	Times	Decrease ; 39	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.40	mm	Main Thickness ;	1.40	mm
Filling Depth :	3.56	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.818	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	34	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.36	kN	Max Punch ;	22
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	38
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	47

Tablet Data (N/A)

Total Counter :	350152	Tablets			
A.W.C Counter :	340031	Tablets			
HEP :	66 (0.0%)	Tablets	LEP :	314 (0.1%)	Tablets
GOOD :	339651 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	pb97604	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	01 Hour 50 Min 48 Sec
Total Counter :	350152	Total Running Time :	2274 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	10.95	kN	No		
HEP :	20.0 %	10.52	kN	Yes	15	Rotations
HCP :	2.0 %	8.94	kN	Yes	20	Times
Ref :		8.76	kN			
LCP :	2.0 %	8.59	kN	Yes	20	Times
LEP :	20.0 %	7.01	kN	Yes	15	Rotations
LSP :	25.0 %	6.57	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.00	kN	Min :	1.95	kN	Punch NO.;	37
SD :	0.80	%	Max :	2.05	kN	Punch NO.;	53
Mean Main Pressure :	8.84	kN	Min :	7.84	kN	Punch NO.;	54
SD :	4.40	%	Max :	10.14	kN	Punch NO.;	10
Filling Depth :	Increase ;	6	Times	Decrease ;	23	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.60	mm
Filling Depth :	4.00	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.818	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	34	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.34	kN	Max Punch ;	24
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	38
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	47

Tablet Data (N/A)

Total Counter :	350152	Tablets			
A.W.C Counter :	340031	Tablets			
HEP :	66 (0.0%)	Tablets	LEP :	314 (0.1%)	Tablets
GOOD :	339651 (99.9%)	Tablets			