

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	pb97604	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	02 Hour 21 Min 38 Sec
Total Counter :	450178	Total Running Time :	2274 Hour 57 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	48	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.74	kN	No		
HEP :	20.0 %	9.35	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	7.95	kN	Yes 15	Times	
Ref :		7.79	kN			
LCP :	2.0 %	7.64	kN	Yes 15	Times	
LEP :	20.0 %	6.23	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	5.85	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.59	kN	Min :	1.44	kN	Punch NO.;	46
SD :	2.90	%	Max :	1.72	kN	Punch NO.;	10
Mean Main Pressure :	7.82	kN	Min :	5.77	kN	Punch NO.;	46
SD :	8.00	%	Max :	9.49	kN	Punch NO.;	10
Filling Depth :	Increase ; 22	Times	Decrease ; 58	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.37	mm	Main Thickness ;	1.37	mm
Filling Depth :	3.63	mm	Current Cam :	Cam B	
Main Air pressure :	0.816	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	34	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.37	kN	Max Punch ;	17
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	38
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	57

Tablet Data (N/A)

Total Counter :	450178	Tablets			
A.W.C Counter :	437296	Tablets			
HEP :	187 (0.0%)	Tablets	LEP :	867 (0.2%)	Tablets
GOOD :	436242 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	pb97604	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	02 Hour 21 Min 38 Sec
Total Counter :	450178	Total Running Time :	2274 Hour 57 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.52	kN	No		
HEP :	20.0 %	9.14	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	7.77	kN	Yes 20	Times	
Ref :		7.62	kN			
LCP :	2.0 %	7.47	kN	Yes 20	Times	
LEP :	20.0 %	6.10	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	5.71	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.80	kN	Min :	1.70	kN	Punch NO.;	26
SD :	1.90	%	Max :	1.89	kN	Punch NO.;	10
Mean Main Pressure :	7.69	kN	Min :	6.30	kN	Punch NO.;	54
SD :	5.50	%	Max :	8.67	kN	Punch NO.;	1
Filling Depth :	Increase ;	10	Times	Decrease ;	38	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.57	mm	Main Thickness ;	1.57	mm
Filling Depth :	3.99	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.816	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	34	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.37	kN	Max Punch ;	17
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	26
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	57

Tablet Data (N/A)

Total Counter :	450178	Tablets			
A.W.C Counter :	437296	Tablets			
HEP :	187 (0.0%)	Tablets	LEP :	867 (0.2%)	Tablets
GOOD :	436242 (99.8%)	Tablets			