

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	rp98927	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	06 Hour 59 Min 01 Sec
Total Counter :	1350682	Total Running Time :	2279 Hour 35 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.54	kN	No		
HEP :	20.0 %	9.16	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	7.75	kN	Yes 15	Times	
Ref :		7.63	kN			
LCP :	1.5 %	7.52	kN	Yes 15	Times	
LEP :	20.0 %	6.11	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	5.72	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.52	kN	Min :	1.36	kN	Punch NO.;	24
SD :	3.10	%	Max :	1.61	kN	Punch NO.;	58
Mean Main Pressure :	7.66	kN	Min :	5.63	kN	Punch NO.;	31
SD :	8.70	%	Max :	8.74	kN	Punch NO.;	2
Filling Depth :	Increase ; 56	Times	Decrease ;	110	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.37	mm	Main Thickness ;	1.37	mm
Filling Depth :	3.41	mm	Current Cam :	Cam B	
Main Air pressure :	0.815	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	161	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.33	kN		
	Max ;	0.37	kN	Max Punch ;	17
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	4
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	55

Tablet Data (N/A)

Total Counter :	1350682	Tablets			
A.W.C Counter :	1334344	Tablets			
HEP :	601 (0.0%)	Tablets	LEP :	13085 (1.0%)	Tablets
GOOD :	1320658 (99.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	rp98927	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	06 Hour 59 Min 01 Sec
Total Counter :	1350682	Total Running Time :	2279 Hour 35 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.91	kN	No		
HEP :	20.0 %	9.52	kN	Yes 15	Rotations 20	Tablets
HCP :	1.5 %	8.05	kN	Yes 20	Times	
Ref :		7.93	kN			
LCP :	1.5 %	7.81	kN	Yes 20	Times	
LEP :	20.0 %	6.34	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	5.95	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.74	kN	Min :	1.61	kN	Punch NO.;	24
SD :	2.10	%	Max :	1.85	kN	Punch NO.;	48
Mean Main Pressure :	7.90	kN	Min :	6.43	kN	Punch NO.;	55
SD :	5.70	%	Max :	8.84	kN	Punch NO.;	48
Filling Depth :	Increase ;	143	Times	Decrease ;	161	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.57	mm	Main Thickness ;	1.57	mm
Filling Depth :	3.93	mm	Current Cam :	Cam B	
Main Air pressure :	0.815	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	161	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.33	kN		
	Max ;	0.37	kN	Max Punch ;	17
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	38
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	55

Tablet Data (N/A)

Total Counter :	1350682	Tablets			
A.W.C Counter :	1334344	Tablets			
HEP :	601 (0.0%)	Tablets	LEP :	13085 (1.0%)	Tablets
GOOD :	1320658 (99.0%)	Tablets			