

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	rp98927	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	08 Hour 15 Min 54 Sec
Total Counter :	1600912	Total Running Time :	2280 Hour 52 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	11.25	kN	No		
HEP :	20.0 %	10.80	kN	Yes	10	Rotations 20 Tablets
HCP :	1.5 %	9.13	kN	Yes	15	Times
Ref :		9.00	kN			
LCP :	1.5 %	8.86	kN	Yes	15	Times
LEP :	20.0 %	7.20	kN	No	15	Rotations 20 Tablets
LSP :	25.0 %	6.75	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.60	kN	Min :	1.39	kN	Punch NO.;	27
SD :	4.20	%	Max :	1.70	kN	Punch NO.;	35
Mean Main Pressure :	8.89	kN	Min :	6.22	kN	Punch NO.;	27
SD :	9.90	%	Max :	10.19	kN	Punch NO.;	6
Filling Depth :	Increase ;	60	Times	Decrease ;	117	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.37	mm	Main Thickness ;	1.37	mm
Filling Depth :	3.96	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	84	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.36	kN	Max Punch ;	34
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	23
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	22

Tablet Data (N/A)

Total Counter :	1600912	Tablets			
A.W.C Counter :	1584529	Tablets			
HEP :	665 (0.0%)	Tablets	LEP :	20265 (1.3%)	Tablets
GOOD :	1563599 (98.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	rp98927	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	08 Hour 15 Min 54 Sec
Total Counter :	1600912	Total Running Time :	2280 Hour 52 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	11.27	kN	No		
HEP :	20.0 %	10.82	kN	Yes 15	Rotations 20	Tablets
HCP :	1.5 %	9.15	kN	Yes 20	Times	
Ref :		9.01	kN			
LCP :	1.5 %	8.88	kN	Yes 20	Times	
LEP :	20.0 %	7.21	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	6.76	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.83	kN	Min :	1.73	kN	Punch NO.;	24
SD :	2.20	%	Max :	1.95	kN	Punch NO.;	46
Mean Main Pressure :	9.04	kN	Min :	7.26	kN	Punch NO.;	55
SD :	5.40	%	Max :	9.82	kN	Punch NO.;	46
Filling Depth :	Increase ;	163	Times	Decrease ;	183	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.57	mm	Main Thickness ;	1.57	mm
Filling Depth :	4.06	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	84	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.36	kN	Max Punch ;	36
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	23
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	22

Tablet Data (N/A)

Total Counter :	1600912	Tablets			
A.W.C Counter :	1584529	Tablets			
HEP :	665 (0.0%)	Tablets	LEP :	20265 (1.3%)	Tablets
GOOD :	1563599 (98.7%)	Tablets			