

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	ks99394	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	11 Hour 35 Min 42 Sec
Total Counter :	2251158	Total Running Time :	2284 Hour 12 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.53	kN	No		
HEP :	20.0 %	9.15	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	7.74	kN	Yes 15	Times	
Ref :		7.63	kN			
LCP :	1.5 %	7.51	kN	Yes 15	Times	
LEP :	20.0 %	6.10	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	5.72	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.61	kN	Min :	1.40	kN	Punch NO.;	47
SD :	4.10	%	Max :	1.72	kN	Punch NO.;	6
Mean Main Pressure :	7.67	kN	Min :	4.76	kN	Punch NO.;	47
SD :	11.00	%	Max :	8.94	kN	Punch NO.;	35
Filling Depth :	Increase ; 79	Times	Decrease ;	146	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.37	mm	Main Thickness ;	1.37	mm
Filling Depth :	3.66	mm	Current Cam :	Cam B	
Main Air pressure :	0.803	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	74	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.38	kN	Max Punch ;	24
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	47
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	2251158	Tablets			
A.W.C Counter :	2233659	Tablets			
HEP :	850 (0.0%)	Tablets	LEP :	38514 (1.7%)	Tablets
GOOD :	2194295 (98.2%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	ks99394	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	11 Hour 35 Min 42 Sec
Total Counter :	2251158	Total Running Time :	2284 Hour 12 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.92	kN	No		
HEP :	20.0 %	9.52	kN	Yes 15	Rotations 20	Tablets
HCP :	1.5 %	8.05	kN	Yes 20	Times	
Ref :		7.93	kN			
LCP :	1.5 %	7.82	kN	Yes 20	Times	
LEP :	20.0 %	6.35	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	5.95	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.83	kN	Min :	1.78	kN	Punch NO.;	18
SD :	2.00	%	Max :	1.93	kN	Punch NO.;	1
Mean Main Pressure :	7.93	kN	Min :	6.61	kN	Punch NO.;	18
SD :	5.20	%	Max :	8.53	kN	Punch NO.;	1
Filling Depth :	Increase ;	209	Times	Decrease ;	230	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.57	mm	Main Thickness ;	1.57	mm
Filling Depth :	4.03	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.803	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	74	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.31	kN		
	Max ;	0.36	kN	Max Punch ;	50
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	47
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	2251158	Tablets			
A.W.C Counter :	2233659	Tablets			
HEP :	850 (0.0%)	Tablets	LEP :	38514 (1.7%)	Tablets
GOOD :	2194295 (98.2%)	Tablets			