

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	os190259	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	02 Hour 32 Min 50 Sec
Total Counter :	400198	Total Running Time :	2307 Hour 17 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	75	%	Manual ;	57	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.38	kN	No		
HEP :	25.0 %	26.33	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	21.49	kN	Yes 20	Times	
Ref :		21.06	kN			
LCP :	2.0 %	20.64	kN	Yes 20	Times	
LEP :	25.0 %	15.80	kN	Yes 15	Rotations 20	Tablets
LSP :	35.0 %	13.69	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.42	kN	Min :	2.27	kN	Punch NO.;	47
SD :	3.20	%	Max :	2.55	kN	Punch NO.;	16
Mean Main Pressure :	20.46	kN	Min :	18.37	kN	Punch NO.;	47
SD :	3.40	%	Max :	21.91	kN	Punch NO.;	38
Filling Depth :	Increase ;	289	Times	Decrease ;	244	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.20	mm	Main Thickness ;	2.20	mm
Filling Depth :	8.40	mm	Current Cam :	Cam C	
Main Air pressure :	0.822	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	46
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	17
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	400198	Tablets			
A.W.C Counter :	388114	Tablets			
HEP :	399 (0.1%)	Tablets	LEP :	419 (0.1%)	Tablets
GOOD :	387296 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	os190259	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	02 Hour 32 Min 50 Sec
Total Counter :	400198	Total Running Time :	2307 Hour 17 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	82	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	26.86	kN	No		
HEP :	25.0 %	26.86	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	21.92	kN	Yes 20	Times	
Ref :		21.49	kN			
LCP :	2.0 %	21.06	kN	Yes 20	Times	
LEP :	25.0 %	16.12	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	16.12	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.65	kN	Min :	2.52	kN	Punch NO.;	19
SD :	2.90	%	Max :	2.81	kN	Punch NO.;	50
Mean Main Pressure :	21.46	kN	Min :	20.09	kN	Punch NO.;	37
SD :	3.80	%	Max :	23.24	kN	Punch NO.;	7
Filling Depth :	Increase ;	314	Times	Decrease ;	228	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	8.54	mm	Current Cam :	Cam C	
Main Air pressure :	0.822	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.20	kN	Max Punch ;	47
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	17
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	400198	Tablets			
A.W.C Counter :	388114	Tablets			
HEP :	399 (0.1%)	Tablets	LEP :	419 (0.1%)	Tablets
GOOD :	387296 (99.8%)	Tablets			