

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	os190259	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	02 Hour 51 Min 43 Sec
Total Counter :	450222	Total Running Time :	2307 Hour 36 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	75	%	Manual ;	57	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.38	kN	No		
HEP :	25.0 %	26.33	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	21.49	kN	Yes 20	Times	
Ref :		21.06	kN			
LCP :	2.0 %	20.64	kN	Yes 20	Times	
LEP :	25.0 %	15.80	kN	Yes 15	Rotations 20	Tablets
LSP :	35.0 %	13.69	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.48	kN	Min :	2.32	kN	Punch NO.;	1
SD :	3.10	%	Max :	2.68	kN	Punch NO.;	18
Mean Main Pressure :	21.29	kN	Min :	19.13	kN	Punch NO.;	5
SD :	3.70	%	Max :	23.38	kN	Punch NO.;	18
Filling Depth :	Increase ;	331	Times	Decrease ;	293	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.20	mm	Main Thickness ;	2.20	mm
Filling Depth :	8.31	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.825	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.22	kN	Max Punch ;	44
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	10
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	450222	Tablets			
A.W.C Counter :	437912	Tablets			
HEP :	401 (0.1%)	Tablets	LEP :	419 (0.1%)	Tablets
GOOD :	437092 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	os190259	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	02 Hour 51 Min 43 Sec
Total Counter :	450222	Total Running Time :	2307 Hour 36 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	82	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	26.86	kN	No		
HEP :	25.0 %	26.86	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	21.92	kN	Yes 20	Times	
Ref :		21.49	kN			
LCP :	2.0 %	21.06	kN	Yes 20	Times	
LEP :	25.0 %	16.12	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	16.12	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.74	kN	Min :	2.52	kN	Punch NO.;	12
SD :	3.20	%	Max :	2.93	kN	Punch NO.;	39
Mean Main Pressure :	22.58	kN	Min :	20.27	kN	Punch NO.;	12
SD :	3.90	%	Max :	24.63	kN	Punch NO.;	39
Filling Depth :	Increase ;	360	Times	Decrease ;	275	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	8.40	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.825	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.23	kN	Max Punch ;	46
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	10
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	450222	Tablets			
A.W.C Counter :	437912	Tablets			
HEP :	401 (0.1%)	Tablets	LEP :	419 (0.1%)	Tablets
GOOD :	437092 (99.8%)	Tablets			