

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	vy190186	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	06 Hour 02 Min 10 Sec
Total Counter :	950404	Total Running Time :	2310 Hour 47 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	57	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.16	kN	No		
HEP :	25.0 %	20.34	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	16.60	kN	Yes 20	Times	
Ref :		16.28	kN			
LCP :	2.0 %	15.95	kN	Yes 20	Times	
LEP :	25.0 %	12.21	kN	Yes 15	Rotations 20	Tablets
LSP :	35.0 %	10.58	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.38	kN	Min :	2.21	kN	Punch NO.;	13
SD :	2.80	%	Max :	2.54	kN	Punch NO.;	17
Mean Main Pressure :	15.68	kN	Min :	14.51	kN	Punch NO.;	52
SD :	3.10	%	Max :	16.88	kN	Punch NO.;	17
Filling Depth :	Increase ;	597	Times	Decrease ;	527	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	6.91	mm	Current Cam :	Cam C	
Main Air pressure :	0.832	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	36	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	48
Lower Punch :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	34
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.11	kN	Max Punch ;	30

Tablet Data (N/A)

Total Counter :	950404	Tablets			
A.W.C Counter :	931940	Tablets			
HEP :	688 (0.1%)	Tablets	LEP :	493 (0.1%)	Tablets
GOOD :	930759 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	vy190186	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	06 Hour 02 Min 10 Sec
Total Counter :	950404	Total Running Time :	2310 Hour 47 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	50	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	27.73	kN	No		
HEP :	25.0 %	27.73	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	22.63	kN	Yes 20	Times	
Ref :		22.19	kN			
LCP :	2.0 %	21.74	kN	Yes 20	Times	
LEP :	25.0 %	16.64	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	16.64	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.65	kN	Min :	2.42	kN	Punch NO.;	2
		3.50	%	Max :	2.93	kN	Punch NO.;	34
Mean Main Pressure :	SD :	21.80	kN	Min :	19.48	kN	Punch NO.;	2
		3.90	%	Max :	23.79	kN	Punch NO.;	34
Filling Depth :	Increase ;	662	Times	Decrease ;	538	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	8.18	mm	Current Cam :	Cam C	
Main Air pressure :	0.832	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	36	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	48
Lower Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	34
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.11	kN	Max Punch ;	30

Tablet Data (N/A)

Total Counter :	950404	Tablets			
A.W.C Counter :	931940	Tablets			
HEP :	688 (0.1%)	Tablets	LEP :	493 (0.1%)	Tablets
GOOD :	930759 (99.9%)	Tablets			