

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	sj97904	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	07 Hour 55 Min 24 Sec
Total Counter :	1250566	Total Running Time :	2312 Hour 40 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	54	%	Manual ;	57	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.41	kN	No		
HEP :	25.0 %	26.36	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	21.51	kN	Yes 20	Times	
Ref :		21.09	kN			
LCP :	2.0 %	20.67	kN	Yes 20	Times	
LEP :	25.0 %	15.82	kN	Yes 15	Rotations 20	Tablets
LSP :	35.0 %	13.71	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.50	kN	Min :	2.27	kN	Punch NO.;	49
SD :	4.30	%	Max :	2.76	kN	Punch NO.;	17
Mean Main Pressure :	21.58	kN	Min :	19.41	kN	Punch NO.;	2
SD :	4.90	%	Max :	23.94	kN	Punch NO.;	17
Filling Depth :	Increase ;	1009	Times	Decrease ;	889	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	8.42	mm	Current Cam :	Cam C	
Main Air pressure :	0.844	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.20	kN	Max Punch ;	46
Lower Punch :	Average ;	0.04	kN		
	Max ;	0.29	kN	Max Punch ;	35
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	1250566	Tablets			
A.W.C Counter :	1229809	Tablets			
HEP :	955 (0.1%)	Tablets	LEP :	617 (0.1%)	Tablets
GOOD :	1228237 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	sj97904	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	07 Hour 55 Min 24 Sec
Total Counter :	1250566	Total Running Time :	2312 Hour 40 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	50	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	27.73	kN	No		
HEP :	25.0 %	27.73	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	22.63	kN	Yes 20	Times	
Ref :		22.19	kN			
LCP :	2.0 %	21.74	kN	Yes 20	Times	
LEP :	25.0 %	16.64	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	16.64	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.74	kN	Min :	2.53	kN	Punch NO.;	38
SD :	4.50	%	Max :	3.23	kN	Punch NO.;	51
Mean Main Pressure :	22.33	kN	Min :	20.63	kN	Punch NO.;	38
SD :	5.10	%	Max :	26.53	kN	Punch NO.;	51
Filling Depth :	Increase ;	1031	Times	Decrease ;	816	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	9.65	mm	Current Cam :	Cam C	
Main Air pressure :	0.844	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.20	kN	Max Punch ;	46
Lower Punch :	Average ;	0.04	kN		
	Max ;	0.28	kN	Max Punch ;	35
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.14	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	1250566	Tablets			
A.W.C Counter :	1229809	Tablets			
HEP :	955 (0.1%)	Tablets	LEP :	617 (0.1%)	Tablets
GOOD :	1228237 (99.9%)	Tablets			