

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	os190259	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	11 Hour 44 Min 33 Sec
Total Counter :	1788314	Total Running Time :	2316 Hour 27 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	57	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	26.55	kN	No		
HEP :	20.0 %	25.49	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	21.67	kN	Yes 20	Times	
Ref :		21.24	kN			
LCP :	2.0 %	20.82	kN	Yes 20	Times	
LEP :	20.0 %	16.99	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	15.93	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.45	kN	Min :	2.29	kN	Punch NO.;	37
SD :	2.90	%	Max :	2.60	kN	Punch NO.;	51
Mean Main Pressure :	21.26	kN	Min :	19.97	kN	Punch NO.;	30
SD :	3.10	%	Max :	22.52	kN	Punch NO.;	40
Filling Depth :	Increase ;	57	Times	Decrease ;	54	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	9.10	mm	Current Cam :	Cam C	
Main Air pressure :	0.836	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.19	kN	Max Punch ;	42
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.14	kN	Max Punch ;	35
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.11	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	1788314	Tablets			
A.W.C Counter :	1761976	Tablets			
HEP :	3269 (0.2%)	Tablets	LEP :	742 (0.0%)	Tablets
GOOD :	1757965 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	os190259	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	11 Hour 44 Min 33 Sec
Total Counter :	1788314	Total Running Time :	2316 Hour 27 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	57	%	Manual ;	50	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	26.80	kN	No		
HEP :	20.0 %	25.73	kN	Yes	15	Rotations
HCP :	2.0 %	21.87	kN	Yes	20	Times
Ref :		21.44	kN			
LCP :	2.0 %	21.01	kN	Yes	20	Times
LEP :	20.0 %	17.15	kN	Yes	15	Rotations
LSP :	25.0 %	16.08	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.72	kN	Min :	2.53	kN	Punch NO.;	37
SD :	2.80	%	Max :	2.86	kN	Punch NO.;	34
Mean Main Pressure :	21.98	kN	Min :	20.55	kN	Punch NO.;	47
SD :	3.10	%	Max :	23.64	kN	Punch NO.;	18
Filling Depth :	Increase ;	32	Times	Decrease ;	36	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	9.41	mm	Current Cam :	Cam C	
Main Air pressure :	0.836	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.19	kN	Max Punch ;	42
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.14	kN	Max Punch ;	35
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.11	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	1788314	Tablets			
A.W.C Counter :	1761976	Tablets			
HEP :	3269 (0.2%)	Tablets	LEP :	742 (0.0%)	Tablets
GOOD :	1757965 (99.8%)	Tablets			