

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	rp98927	Batch NO. :	IUM2501040
Print Interval :	50000 Tablets	Running Time :	09 Hour 28 Min 16 Sec
Total Counter :	1201482	Total Running Time :	2327 Hour 22 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	57	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	27.11	kN	No		
HEP :	20.0 %	26.03	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	22.12	kN	Yes 20	Times	
Ref :		21.69	kN			
LCP :	2.0 %	21.26	kN	Yes 20	Times	
LEP :	20.0 %	17.35	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	16.27	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.49	kN	Min :	2.38	kN	Punch NO.;	37
SD :	2.40	%	Max :	2.65	kN	Punch NO.;	27
Mean Main Pressure :	21.29	kN	Min :	20.22	kN	Punch NO.;	37
SD :	2.60	%	Max :	22.54	kN	Punch NO.;	27
Filling Depth :	Increase ;	663	Times	Decrease ;	551	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	9.94	mm	Current Cam :	Cam C	
Main Air pressure :	0.793	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.20	kN	Max Punch ;	39
Lower Punch :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	35
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	1201482	Tablets			
A.W.C Counter :	1194737	Tablets			
HEP :	3731 (0.3%)	Tablets	LEP :	534 (0.0%)	Tablets
GOOD :	1190472 (99.6%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	rp98927	Batch NO. :	IUM2501040
Print Interval :	50000 Tablets	Running Time :	09 Hour 28 Min 16 Sec
Total Counter :	1201482	Total Running Time :	2327 Hour 22 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	50	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	27.97	kN	No		
HEP :	20.0 %	26.85	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	22.83	kN	Yes 20	Times	
Ref :		22.38	kN			
LCP :	2.0 %	21.93	kN	Yes 20	Times	
LEP :	20.0 %	17.90	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	16.78	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.82	kN	Min :	2.66	kN	Punch NO.;	37
SD :	2.70	%	Max :	2.97	kN	Punch NO.;	51
Mean Main Pressure :	22.33	kN	Min :	20.64	kN	Punch NO.;	37
SD :	3.60	%	Max :	23.76	kN	Punch NO.;	11
Filling Depth :	Increase ;	541	Times	Decrease ;	406	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	9.74	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.793	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.20	kN	Max Punch ;	39
Lower Punch :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	35
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	1201482	Tablets			
A.W.C Counter :	1194737	Tablets			
HEP :	3731 (0.3%)	Tablets	LEP :	534 (0.0%)	Tablets
GOOD :	1190472 (99.6%)	Tablets			