

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | IBU BP400MG<br>STIU2B00 |
| User ID :        | rp98927       | Batch NO. :          | IUM2501040              |
| Print Interval : | 50000 Tablets | Running Time :       | 10 Hour 39 Min 12 Sec   |
| Total Counter :  | 1351536       | Total Running Time : | 2328 Hour 33 Min        |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 80       | %       | Manual ;           | 57           | RPM       |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |             | 8.5-14mm |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |             | 2025000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 50       | Min     | Supply Time ;      | 0.5          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 30       | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 60.0     | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 25.0 %      | 27.11    | kN      | No                 |              |           |
| HEP :                              | 20.0 %      | 26.03    | kN      | Yes 10             | Rotations 20 | Tablets   |
| HCP :                              | 2.0 %       | 22.12    | kN      | Yes 20             | Times        |           |
| Ref :                              |             | 21.69    | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 21.26    | kN      | Yes 20             | Times        |           |
| LEP :                              | 20.0 %      | 17.35    | kN      | Yes 15             | Rotations 20 | Tablets   |
| LSP :                              | 25.0 %      | 16.27    | kN      | No                 |              |           |
| SD limit :                         | 45.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 40.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.50       | kN  | Min : | 2.32       | kN  | Punch NO.; | 37 |
| SD :                 | 2.90       | %   | Max : | 2.73       | kN  | Punch NO.; | 7  |
| Mean Main Pressure : | 21.67      | kN  | Min : | 19.59      | kN  | Punch NO.; | 37 |
| SD :                 | 3.20       | %   | Max : | 24.00      | kN  | Punch NO.; | 7  |
| Filling Depth :      | Increase ; | 805 | Times | Decrease ; | 671 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |        |     |                  |          |              |
|-------------------------------|--------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20     | RPM | Capacity :       | 127200   | Tablets/hour |
| Feeder : Status ;             | Auto   |     | Speed ;          | 16       | RPM          |
| Pre Upper Punch Position ;    | 2.99   | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.80   | mm  | Pre Thickness ;  | 2.81     | mm           |
| Main Upper Punch Position ;   | 2.99   | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.38   | mm  | Main Thickness ; | 2.39     | mm           |
| Filling Depth :               | 8.95   | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.821  | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |        |     |                  |          |              |
| Upper Punch Remain Time (S1): | 26     | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 18     | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0      | Min |                  |          |              |
| Powder Status :               | Enable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off    |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.05 | kN |             |    |
|                  | Max ;     | 0.21 | kN | Max Punch ; | 28 |
| Lower Punch :    | Average ; | 0.06 | kN |             |    |
|                  | Max ;     | 0.11 | kN | Max Punch ; | 35 |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.09 | kN | Max Punch ; | 35 |

### Tablet Data (N/A)

|                 |                 |         |       |            |         |
|-----------------|-----------------|---------|-------|------------|---------|
| Total Counter : | 1351536         | Tablets |       |            |         |
| A.W.C Counter : | 1343151         | Tablets |       |            |         |
| HEP :           | 3853 (0.3%)     | Tablets | LEP : | 831 (0.1%) | Tablets |
| GOOD :          | 1338467 (99.7%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | IBU BP400MG<br>STIU2B00 |
| User ID :        | rp98927       | Batch NO. :          | IUM2501040              |
| Print Interval : | 50000 Tablets | Running Time :       | 10 Hour 39 Min 12 Sec   |
| Total Counter :  | 1351536       | Total Running Time : | 2328 Hour 33 Min        |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 80        | %       | Manual ;           | 50           | RPM       |
| Filling Cam :                      |        | Cam C     |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |        | 8.5-14mm  |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |        | 2025000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.400     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 50        | Min     | Supply Time ;      | 0.5          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 30        | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 60.0      | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 25.0 % | 27.97     | kN      | No                 |              |           |
| HEP :                              | 20.0 % | 26.85     | kN      | Yes 15             | Rotations 20 | Tablets   |
| HCP :                              | 2.0 %  | 22.83     | kN      | Yes 20             | Times        |           |
| Ref :                              |        | 22.38     | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 21.93     | kN      | Yes 20             | Times        |           |
| LEP :                              | 20.0 % | 17.90     | kN      | Yes 15             | Rotations 20 | Tablets   |
| LSP :                              | 25.0 % | 16.78     | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 40.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | N      |           |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.85       | kN  | Min : | 2.69       | kN  | Punch NO.; | 23 |
| SD :                 | 2.90       | %   | Max : | 3.05       | kN  | Punch NO.; | 44 |
| Mean Main Pressure : | 22.77      | kN  | Min : | 21.27      | kN  | Punch NO.; | 23 |
| SD :                 | 3.30       | %   | Max : | 24.80      | kN  | Punch NO.; | 7  |
| Filling Depth :      | Increase ; | 649 | Times | Decrease ; | 481 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20      | RPM | Capacity :       | 127200   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 16       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.80    | mm  | Pre Thickness ;  | 2.81     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.40    | mm  | Main Thickness ; | 2.41     | mm           |
| Filling Depth :               | 9.03    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.821   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 26      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 18      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.05 | kN |             |    |
|                  | Max ;     | 0.22 | kN | Max Punch ; | 39 |
| Lower Punch :    | Average ; | 0.06 | kN |             |    |
|                  | Max ;     | 0.11 | kN | Max Punch ; | 35 |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.09 | kN | Max Punch ; | 35 |

### Tablet Data (N/A)

|                 |                 |         |       |            |         |
|-----------------|-----------------|---------|-------|------------|---------|
| Total Counter : | 1351536         | Tablets |       |            |         |
| A.W.C Counter : | 1343151         | Tablets |       |            |         |
| HEP :           | 3853 (0.3%)     | Tablets | LEP : | 831 (0.1%) | Tablets |
| GOOD :          | 1338467 (99.7%) | Tablets |       |            |         |