

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	sj97904	Batch NO. :	IUM2501040
Print Interval :	50000 Tablets	Running Time :	14 Hour 11 Min 55 Sec
Total Counter :	1801658	Total Running Time :	2332 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	57	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	27.11	kN	No		
HEP :	20.0 %	26.03	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	22.12	kN	Yes 20	Times	
Ref :		21.69	kN			
LCP :	2.0 %	21.26	kN	Yes 20	Times	
LEP :	20.0 %	17.35	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	16.27	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.47	kN	Min :	2.27	kN	Punch NO.;	28
SD :	3.20	%	Max :	2.65	kN	Punch NO.;	44
Mean Main Pressure :	21.51	kN	Min :	19.12	kN	Punch NO.;	28
SD :	3.80	%	Max :	23.12	kN	Punch NO.;	51
Filling Depth :	Increase ;	1047	Times	Decrease ;	924	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	8.65	mm	Current Cam :	Cam C	
Main Air pressure :	0.804	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.24	kN	Max Punch ;	13
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	28
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.09	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1801658	Tablets			
A.W.C Counter :	1792792	Tablets			
HEP :	3861 (0.2%)	Tablets	LEP :	832 (0.0%)	Tablets
GOOD :	1788099 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	sj97904	Batch NO. :	IUM2501040
Print Interval :	50000 Tablets	Running Time :	14 Hour 11 Min 55 Sec
Total Counter :	1801658	Total Running Time :	2332 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	50	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	27.97	kN	No		
HEP :	20.0 %	26.85	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	22.83	kN	Yes 20	Times	
Ref :		22.38	kN			
LCP :	2.0 %	21.93	kN	Yes 20	Times	
LEP :	20.0 %	17.90	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	16.78	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.73	kN	Min :	2.60	kN	Punch NO.;	2
SD :	2.50	%	Max :	2.91	kN	Punch NO.;	51
Mean Main Pressure :	21.67	kN	Min :	20.44	kN	Punch NO.;	49
SD :	2.80	%	Max :	23.38	kN	Punch NO.;	17
Filling Depth :	Increase ;	816	Times	Decrease ;	658	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	8.73	mm	Current Cam :	Cam C	
Main Air pressure :	0.804	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.24	kN	Max Punch ;	13
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	28
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1801658	Tablets			
A.W.C Counter :	1792792	Tablets			
HEP :	3861 (0.2%)	Tablets	LEP :	832 (0.0%)	Tablets
GOOD :	1788099 (99.7%)	Tablets			