

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2501140
Print Interval :	50000 Tablets	Running Time :	02 Hour 45 Min 35 Sec
Total Counter :	350142	Total Running Time :	2336 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	86	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	27.04	kN	No		
HEP :	20.0 %	25.96	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	22.07	kN	Yes 20	Times	
Ref :		21.64	kN			
LCP :	2.0 %	21.20	kN	Yes 20	Times	
LEP :	20.0 %	17.31	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	16.23	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.49	kN	Min :	2.33	kN	Punch NO.;	13
SD :	2.60	%	Max :	2.64	kN	Punch NO.;	34
Mean Main Pressure :	21.91	kN	Min :	20.34	kN	Punch NO.;	23
SD :	3.20	%	Max :	23.47	kN	Punch NO.;	7
Filling Depth :	Increase ;	1404	Times	Decrease ;	1259	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	6.88	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.19	kN	Max Punch ;	17
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.10	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	350142	Tablets			
A.W.C Counter :	348595	Tablets			
HEP :	9 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	348586 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2501140
Print Interval :	50000 Tablets	Running Time :	02 Hour 45 Min 35 Sec
Total Counter :	350142	Total Running Time :	2336 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	26.59	kN	No		
HEP :	20.0 %	25.53	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	21.70	kN	Yes 20	Times	
Ref :		21.27	kN			
LCP :	2.0 %	20.85	kN	Yes 20	Times	
LEP :	20.0 %	17.02	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	15.95	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.80	kN	Min :	2.63	kN	Punch NO.;	47
SD :	2.80	%	Max :	2.98	kN	Punch NO.;	16
Mean Main Pressure :	21.35	kN	Min :	19.72	kN	Punch NO.;	4
SD :	3.30	%	Max :	23.28	kN	Punch NO.;	7
Filling Depth :	Increase ;	1063	Times	Decrease ;	849	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	7.55	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.22	kN	Max Punch ;	30
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.10	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	350142	Tablets			
A.W.C Counter :	348595	Tablets			
HEP :	9 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	348586 (100.0%)	Tablets			