

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	sj97904	Batch NO. :	LCM2502710
Print Interval :	50000 Tablets	Running Time :	05 Hour 50 Min 34 Sec
Total Counter :	550140	Total Running Time :	2363 Hour 58 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	48.00	kN	No		
HEP :	20.0 %	46.08	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	39.17	kN	Yes 20	Times	
Ref :		38.40	kN			
LCP :	2.0 %	37.63	kN	Yes 20	Times	
LEP :	20.0 %	30.72	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	28.80	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.08	kN	Min :	2.03	kN	Punch NO.;	18
		1.10	%	Max :	2.14	kN	Punch NO.;	6
Mean Main Pressure :	SD :	38.33	kN	Min :	36.88	kN	Punch NO.;	36
		1.90	%	Max :	39.57	kN	Punch NO.;	11
Filling Depth :	Increase ;	20	Times	Decrease ;	10	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.65	mm	Main Thickness ;	3.65	mm
Filling Depth :	10.32	mm	Current Cam :	Cam C	
Main Air pressure :	0.818	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550140	Tablets			
A.W.C Counter :	545609	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	37 (0.0%)	Tablets
GOOD :	545570 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	sj97904	Batch NO. :	LCM2502710
Print Interval :	50000 Tablets	Running Time :	05 Hour 50 Min 34 Sec
Total Counter :	550140	Total Running Time :	2363 Hour 58 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	163	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	47.74	kN	No		
HEP :	20.0 %	45.83	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	38.96	kN	Yes 20	Times	
Ref :		38.19	kN			
LCP :	2.0 %	37.43	kN	Yes 20	Times	
LEP :	20.0 %	30.56	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	28.65	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.24	kN	Min :	2.17	kN	Punch NO.;	30
SD :	1.30	%	Max :	2.29	kN	Punch NO.;	40
Mean Main Pressure :	38.07	kN	Min :	36.50	kN	Punch NO.;	33
SD :	2.10	%	Max :	40.03	kN	Punch NO.;	37
Filling Depth :	Increase ; 9	Times	Decrease ; 7	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.85	mm	Main Thickness ;	3.85	mm
Filling Depth :	10.08	mm	Current Cam :	Cam C	
Main Air pressure :	0.818	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550140	Tablets			
A.W.C Counter :	545609	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	37 (0.0%)	Tablets
GOOD :	545570 (100.0%)	Tablets			