

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	ps99585	Batch NO. :	LCM2502810
Print Interval :	50000 Tablets	Running Time :	05 Hour 40 Min 16 Sec
Total Counter :	533794	Total Running Time :	2370 Hour 41 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	162	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	46.65	kN	No		
HEP :	20.0 %	44.79	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	38.07	kN	Yes 20	Times	
Ref :		37.32	kN			
LCP :	2.0 %	36.57	kN	Yes 20	Times	
LEP :	20.0 %	29.86	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	27.99	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.10	kN	Min :	2.04	kN	Punch NO.;	30
SD :	1.20	%	Max :	2.15	kN	Punch NO.;	42
Mean Main Pressure :	37.84	kN	Min :	36.22	kN	Punch NO.;	42
SD :	2.10	%	Max :	39.34	kN	Punch NO.;	37
Filling Depth :	Increase ; 54	Times	Decrease ;	76	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.65	mm	Main Thickness ;	3.66	mm
Filling Depth :	10.02	mm	Current Cam :	Cam C	
Main Air pressure :	0.817	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.14	kN	Max Punch ;	17
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	533794	Tablets			
A.W.C Counter :	527977	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	527977 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	ps99585	Batch NO. :	LCM2502810
Print Interval :	50000 Tablets	Running Time :	05 Hour 40 Min 16 Sec
Total Counter :	533794	Total Running Time :	2370 Hour 41 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	163	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	46.92	kN	No		
HEP :	20.0 %	45.05	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	38.29	kN	Yes 20	Times	
Ref :		37.54	kN			
LCP :	2.0 %	36.79	kN	Yes 20	Times	
LEP :	20.0 %	30.03	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	28.15	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.25	kN	Min :	2.18	kN	Punch NO.;	20
		1.60	%	Max :	2.33	kN	Punch NO.;	53
Mean Main Pressure :		37.54	kN	Min :	36.06	kN	Punch NO.;	15
	SD :	2.50	%	Max :	40.44	kN	Punch NO.;	53
Filling Depth :	Increase ;	38	Times	Decrease ;	41	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.84	mm	Main Thickness ;	3.85	mm
Filling Depth :	10.44	mm	Current Cam :	Cam C	
Main Air pressure :	0.817	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.14	kN	Max Punch ;	17
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	533794	Tablets			
A.W.C Counter :	527977	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	527977 (100.0%)	Tablets			