

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	pb97604	Batch NO. :	LCM2502910
Print Interval :	50000 Tablets	Running Time :	01 Hour 29 Min 35 Sec
Total Counter :	150036	Total Running Time :	2373 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	153	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	49.33	kN	No		
HEP :	20.0 %	47.36	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	40.25	kN	Yes 20	Times	
Ref :		39.46	kN			
LCP :	2.0 %	38.67	kN	Yes 20	Times	
LEP :	20.0 %	31.57	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	29.60	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.12	kN	Min :	2.08	kN	Punch NO.;	13
		1.10	%	Max :	2.18	kN	Punch NO.;	46
Mean Main Pressure :		39.73	kN	Min :	37.72	kN	Punch NO.;	33
	SD :	2.10	%	Max :	41.40	kN	Punch NO.;	1
Filling Depth :	Increase ;	65	Times	Decrease ;	152	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.60	mm	Main Thickness ;	3.61	mm
Filling Depth :	10.19	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.813	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.14	kN	Max Punch ;	32
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.02	kN	Max Punch ;	2

Tablet Data (N/A)

Total Counter :	150036	Tablets			
A.W.C Counter :	74113	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	74113 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	pb97604	Batch NO. :	LCM2502910
Print Interval :	50000 Tablets	Running Time :	01 Hour 29 Min 35 Sec
Total Counter :	150036	Total Running Time :	2373 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	158	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	50.28	kN	No		
HEP :	20.0 %	48.27	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	41.03	kN	Yes 20	Times	
Ref :		40.22	kN			
LCP :	2.0 %	39.42	kN	Yes 20	Times	
LEP :	20.0 %	32.18	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	30.17	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.24	kN	Min :	2.17	kN	Punch NO.;	29
		1.60	%	Max :	2.32	kN	Punch NO.;	40
Mean Main Pressure :	SD :	39.79	kN	Min :	38.16	kN	Punch NO.;	17
		3.00	%	Max :	43.39	kN	Punch NO.;	53
Filling Depth :	Increase ;	55	Times	Decrease ;	92	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.75	mm	Main Thickness ;	3.76	mm
Filling Depth :	10.21	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.813	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.15	kN	Max Punch ;	32
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.02	kN	Max Punch ;	25

Tablet Data (N/A)

Total Counter :	150036	Tablets			
A.W.C Counter :	74113	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	74113 (100.0%)	Tablets			