

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2502910
Print Interval :	50000 Tablets	Running Time :	05 Hour 38 Min 36 Sec
Total Counter :	550198	Total Running Time :	2377 Hour 37 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	48.69	kN	No		
HEP :	20.0 %	46.75	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	39.73	kN	Yes 20	Times	
Ref :		38.96	kN			
LCP :	2.0 %	38.18	kN	Yes 20	Times	
LEP :	20.0 %	31.16	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	29.22	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.11	kN	Min :	2.05	kN	Punch NO.;	20
		1.20	%	Max :	2.16	kN	Punch NO.;	6
Mean Main Pressure :	SD :	39.50	kN	Min :	37.84	kN	Punch NO.;	33
		1.90	%	Max :	40.90	kN	Punch NO.;	37
Filling Depth :	Increase ;	71	Times	Decrease ;	185	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.60	mm	Main Thickness ;	3.61	mm
Filling Depth :	10.02	mm	Current Cam :	Cam C	
Main Air pressure :	0.816	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.15	kN	Max Punch ;	6
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.02	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	550198	Tablets			
A.W.C Counter :	356285	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	356285 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2502910
Print Interval :	50000 Tablets	Running Time :	05 Hour 38 Min 36 Sec
Total Counter :	550198	Total Running Time :	2377 Hour 37 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	50.15	kN	No		
HEP :	20.0 %	48.14	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	40.92	kN	Yes 20	Times	
Ref :		40.12	kN			
LCP :	2.0 %	39.31	kN	Yes 20	Times	
LEP :	20.0 %	32.09	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	30.09	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.24	kN	Min :	2.16	kN	Punch NO.;	30
		1.30	%	Max :	2.30	kN	Punch NO.;	21
Mean Main Pressure :		40.26	kN	Min :	38.37	kN	Punch NO.;	33
	SD :	2.20	%	Max :	42.86	kN	Punch NO.;	37
Filling Depth :	Increase ;	61	Times	Decrease ;	100	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.75	mm	Main Thickness ;	3.76	mm
Filling Depth :	10.22	mm	Current Cam :	Cam C	
Main Air pressure :	0.816	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.15	kN	Max Punch ;	6
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.02	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	550198	Tablets			
A.W.C Counter :	356338	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	356338 (100.0%)	Tablets			