

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2503210
Print Interval :	50000 Tablets	Running Time :	03 Hour 11 Min 20 Sec
Total Counter :	300078	Total Running Time :	2395 Hour 46 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	181	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	49.86	kN	No		
HEP :	20.0 %	47.86	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	40.68	kN	Yes 20	Times	
Ref :		39.89	kN			
LCP :	2.0 %	39.09	kN	Yes 20	Times	
LEP :	20.0 %	31.91	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	29.91	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.10	kN	Min :	2.04	kN	Punch NO.;	20
SD :	1.40	%	Max :	2.18	kN	Punch NO.;	42
Mean Main Pressure :	40.19	kN	Min :	38.39	kN	Punch NO.;	41
SD :	1.80	%	Max :	41.57	kN	Punch NO.;	19
Filling Depth :	Increase ; 110	Times	Decrease ;	135	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.64	mm	Main Thickness ;	3.65	mm
Filling Depth :	10.08	mm	Current Cam :	Cam C	
Main Air pressure :	0.809	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	70	Min			
Lower Punch Remain Time (S2):	30	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.16	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	36

Tablet Data (N/A)

Total Counter :	300078	Tablets			
A.W.C Counter :	298109	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	298109 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2503210
Print Interval :	50000 Tablets	Running Time :	03 Hour 11 Min 20 Sec
Total Counter :	300078	Total Running Time :	2395 Hour 46 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	185	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	51.35	kN	No		
HEP :	20.0 %	49.30	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	41.90	kN	Yes 20	Times	
Ref :		41.08	kN			
LCP :	2.0 %	40.26	kN	Yes 20	Times	
LEP :	20.0 %	32.87	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	30.81	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.35	kN	Min :	2.30	kN	Punch NO.;	11
		1.30	%	Max :	2.41	kN	Punch NO.;	17
Mean Main Pressure :		41.42	kN	Min :	39.56	kN	Punch NO.;	15
	SD :	2.00	%	Max :	43.83	kN	Punch NO.;	37
Filling Depth :	Increase ;	90	Times	Decrease ;	131	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.78	mm	Main Thickness ;	3.79	mm
Filling Depth :	10.24	mm	Current Cam :	Cam C	
Main Air pressure :	0.809	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	70	Min			
Lower Punch Remain Time (S2):	30	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.16	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	36

Tablet Data (N/A)

Total Counter :	300078	Tablets			
A.W.C Counter :	298109	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	298109 (100.0%)	Tablets			