

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	sj97904	Batch NO. :	LCM2503210
Print Interval :	50000 Tablets	Running Time :	06 Hour 54 Min 35 Sec
Total Counter :	650152	Total Running Time :	2399 Hour 30 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	48.44	kN	No		
HEP :	20.0 %	46.50	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	39.52	kN	Yes 20	Times	
Ref :		38.75	kN			
LCP :	2.0 %	37.97	kN	Yes 20	Times	
LEP :	20.0 %	31.00	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	29.06	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.01	kN	Min :	1.94	kN	Punch NO.;	30
		1.40	%	Max :	2.08	kN	Punch NO.;	1
Mean Main Pressure :	SD :	39.02	kN	Min :	37.30	kN	Punch NO.;	29
		1.80	%	Max :	40.66	kN	Punch NO.;	37
Filling Depth :	Increase ;	147	Times	Decrease ;	157	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.64	mm	Main Thickness ;	3.65	mm
Filling Depth :	9.92	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.19	kN	Max Punch ;	38
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.04	kN	Max Punch ;	40

Tablet Data (N/A)

Total Counter :	650152	Tablets			
A.W.C Counter :	647957	Tablets			
HEP :	0 (0%)	Tablets	LEP :	33 (0.0%)	Tablets
GOOD :	647924 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	sj97904	Batch NO. :	LCM2503210
Print Interval :	50000 Tablets	Running Time :	06 Hour 54 Min 35 Sec
Total Counter :	650152	Total Running Time :	2399 Hour 30 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	162	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	50.06	kN	No		
HEP :	20.0 %	48.06	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	40.85	kN	Yes 20	Times	
Ref :		40.05	kN			
LCP :	2.0 %	39.25	kN	Yes 20	Times	
LEP :	20.0 %	32.04	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	30.04	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.16	kN	Min :	2.10	kN	Punch NO.;	30
SD :	1.30	%	Max :	2.21	kN	Punch NO.;	35
Mean Main Pressure :	40.41	kN	Min :	38.69	kN	Punch NO.;	17
SD :	1.90	%	Max :	42.50	kN	Punch NO.;	37
Filling Depth :	Increase ;	114	Times	Decrease ;	152	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.78	mm	Main Thickness ;	3.79	mm
Filling Depth :	9.92	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.19	kN	Max Punch ;	12
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.03	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	650152	Tablets			
A.W.C Counter :	647957	Tablets			
HEP :	0 (0%)	Tablets	LEP :	33 (0.0%)	Tablets
GOOD :	647924 (100.0%)	Tablets			