

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2503810
Print Interval :	50000 Tablets	Running Time :	01 Hour 32 Min 44 Sec
Total Counter :	400348	Total Running Time :	2408 Hour 8 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	23.31	kN	No		
HEP :	20.0 %	22.38	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.02	kN	Yes 15	Times	
Ref :		18.65	kN			
LCP :	2.0 %	18.28	kN	Yes 15	Times	
LEP :	20.0 %	14.92	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	13.99	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.77	kN	Min :	1.69	kN	Punch NO.;	6
SD :	1.30	%	Max :	1.83	kN	Punch NO.;	10
Mean Main Pressure :	18.88	kN	Min :	16.47	kN	Punch NO.;	56
SD :	3.40	%	Max :	20.01	kN	Punch NO.;	10
Filling Depth :	Increase ; 6	Times	Decrease ; 9	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.51	mm	Main Thickness ;	2.51	mm
Filling Depth :	8.01	mm	Current Cam :	Cam C	
Main Air pressure :	0.815	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	57	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.58	kN		
	Max ;	0.81	kN	Max Punch ;	67
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.26	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	400348	Tablets			
A.W.C Counter :	396316	Tablets			
HEP :	26 (0.0%)	Tablets	LEP :	489 (0.1%)	Tablets
GOOD :	395801 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2503810
Print Interval :	50000 Tablets	Running Time :	01 Hour 32 Min 44 Sec
Total Counter :	400348	Total Running Time :	2408 Hour 8 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	24.36	kN	No		
HEP :	20.0 %	23.39	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.88	kN	Yes 15	Times	
Ref :		19.49	kN			
LCP :	2.0 %	19.10	kN	Yes 15	Times	
LEP :	20.0 %	15.59	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.62	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.96	kN	Min :	1.91	kN	Punch NO.;	12
		1.20	%	Max :	2.02	kN	Punch NO.;	5
Mean Main Pressure :		19.77	kN	Min :	18.01	kN	Punch NO.;	18
	SD :	3.80	%	Max :	21.64	kN	Punch NO.;	5
Filling Depth :	Increase ;	8	Times	Decrease ;	15	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.67	mm	Main Thickness ;	2.67	mm
Filling Depth :	7.88	mm	Current Cam :	Cam C	
Main Air pressure :	0.815	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	57	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.58	kN		
	Max ;	0.81	kN	Max Punch ;	67
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.27	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	400348	Tablets			
A.W.C Counter :	396316	Tablets			
HEP :	26 (0.0%)	Tablets	LEP :	489 (0.1%)	Tablets
GOOD :	395801 (99.9%)	Tablets			